

QuestSpecialty

CHILL OUT

Freezing Penetrating Lubricant

CHILL OUT

Freezing Penetrating Lubricant  
Lubricante Penetrador Congelante

Freezing Action Unlocks Rusted Parts  
Non-conductive • Non-chlorinated  
Low VOC Content

**WARNING/ADVERTENCIA:**  
FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.  
AEROSOL INFLAMABLE. CONTIENE GAS A PRESIÓN; PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 9 OZ. (255 g)

QuestSpecialty Corporation  
P.O. Box 624 • Brenham, TX 77834  
713.896.8188

600005597

SDS AND PRODUCT INFO



*This formula combines rapid freezing and a special penetrating lubricant to easily loosen bound parts. Sprayed areas shrink and create openings to allow the lubricant to penetrate and open up the toughest bonds.*

**TO LOOSEN BOUND PARTS:** Liberal application will loosen threads, tightened fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. The formula will protect against renewed corrosion.

**DIRECTIONS FOR USE:** Shake well before using. Insert extension tube into valve opening and spray liberally on surface to be treated. Concentrate spray on part to be loosened and avoid the surrounding surfaces. Part should be ready to loosen or remove after waiting about 30 seconds. Repeat if required.

**NOTE:** Sudden drop in temperature after spraying may result in cracking of some paint and plastic. Test first in an inconspicuous area.

**MODO DE EMPLEO:** Agite bien antes de usar. Inserte tubo de extensión en la válvula de apertura y rocíe liberalmente en la superficie para ser tratados. Concentre el rocío en la pieza que debe ser aflojado y evite las superficies alrededor. La pieza debe estar lista para aflojar o remover después de esperar 30 segundos. Repita se es requerido.

**NOTA:** Disminución repentina de temperaturas después de rociar puede resultar en craqueo de pintura y plástico. Pruebe primero en área oculta.

**WARNING:** Flammable Aerosol. Contains gas under pressure; May explode if heated. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an

open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.


**ADVERTENCIA:** Aerosol Inflamable. Contiene gas a presión; Puede explotar si se calienta. Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. -No fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni quemar, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada.

**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

**ADVERTENCIA:** Cáncer y daños reproductivos: www.P65Warnings.ca.gov

**CONTAINS (CAS#):** 1,1-Difluoroethane (75-37-6), Polysiloxane (63148-62-9), Methyl Isobutyl Ketone (108-10-1), Tall Oil Fatty Acid (61790-12-3).  
DOM 2025

HEALTH	1
FLAMMABILITY	2
REACTIVITY	1
PERSONAL	A



ITEM 59700001-16AR

Made in USA

