

QuestSpecialty

THUNDER

Organic Foaming
Engine Degreaser

THUNDER

Organic Foaming Engine Degreaser

Organico Espuma
Desengrasante de Máquinas

Dense Clinging Foam - Will Not Run
Spray On - Wash Off

Dissolves Oil, Tar, Grease, Dirt,
Stains, Road Oil

Cleans Gasoline & Diesel Engines,
Metal, Concrete, Brick, Stone

DANGER / PELIGRO:

EXTREMELY FLAMMABLE AEROSOL. CONTAINS
GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

AEROSOL EXTREMADAMENTE INFLAMABLE.

CONTIENE GAS A PRESIÓN;
PUEDE EXPLOTAR SI SE CALIENTA.

NET WT. 17 OZ. (482 g)

QuestSpecialty Corporation
P.O. Box 624 • Brenham, TX 77834
713.896.8188

THUNDER works quickly to emulsify tar, asphalt, grease and oil. This product is safe and easy to use. Spray on and wash off with water. Dense foam allows product to cling to vertical surface allowing for longer contact time. Cleans engines enabling them to run cooler, look better and last longer. Biodegradable and VOC compliant in all 50 states.

GREAT FOR THESE APPLICATIONS:

Engines • Appliances • Road Equipment Exhaust Vents • Motors • Vehicles • Rims Tools
• Refrigeration Coils • Machinery
Industrial Equipment • Concrete • Etc.

DIRECTIONS FOR USE: When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar.

FOR ENGINES: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.

OTHER SURFACES: To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

MODO DE EMPLEO: Cuando se use en superficies pintadas, pruebe en un área pequeña para asegurar que la pintura no sea afectada. Sostenga el bote de 8 a 10 pulgadas del área que se va a rociar. Aplique una capa asegurándose de cubrir toda la grasa, aceite y alquitrán.

PARA MOTORES: Cubra la toma del carburador y el distribuidor con plástico o papel aluminio para evitar contaminación con agua. Permita que el producto actúen por 15 minutos para que ocurra una completa penetración y emulsificación. Limpie con manguera. Remueva el plástico o papel aluminio y encienda el motor por 15 minutos para que se seque bien.

OTRAS SUPERFICIES: Para remover aceite, grasa, alquitrán y asfalto de otras superficies, aplique sobre la superficie cubriendo el área que se va a limpiar. Permita que el producto trabaje por 10 o 15 minutos. Lave con un fuerte chorro de

agua. Áreas muy sucias pueden ser talladas o un segunda aplicación.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
NOTE: This product produces vapors that are flammable when concentrated or confined.

PELIGRO: Aerosol Extremadamente Inflamable. Contiene gas a presión; Puede explotar si se calienta. Causa irritación ocular. Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. -No Fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni queme, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada. Lave las manos en fondo después de utilizar. Si en los ojos: Enjuague cuidadosamente con agua por varios minutos. Remueva lentes de contacto, si están presentes y fáciles de hacer. Continúe enjuagando. Si persiste la irritación ocular: Obtenga atención médica.

NOTA: Este producto produce vapores que son inflamable cuando son concentrado o confinados.

CONTAINS (CAS#): Water (7732-18-5), Propane/n-Butane (68476-86-8), Diethylene glycol n-butyl ether (112-34-5), Distillates (petroleum), hydrotreated light (64742-47-8), Nonionic Surfactant (127087-87-0).

HMIS RATINGS: Health - 1, Flammability - 1, Reactivity - 0, Personal - B.



ITEM 82400001-20AR

Made in USA

600005824