

QuestSpecialty

# CRUNCH

## Organic Gel Engine Degreaser

# CRUNCH

## Organic Gel Engine Degreaser

### Gel Orgánico Desengrasante de Máquinas

**Gel-Base - Will Not Run  
Spray On - Wash Off**

**Dissolves Oil, Tar, Grease,  
Dirt, Stains, Road Oil**

**Cleans Gasoline & Diesel Engines,  
Metal, Concrete, Brick, Stone**

**Contains No Chlorinated or  
Fluorinated Solvents**

**DANGER/PELIGRO:  
FLAMMABLE AEROSOL. CONTAINS GAS  
UNDER PRESSURE. MAY EXPLODE IF HEATED.  
AEROSOL INFLAMMABLE. CONTIENE GAS A  
PRESION. PUEDE EXPLOTAR SI SE CALIENTA.**

**NET WT. 16 OZ. (454 g)**

QuestSpecialty Corporation  
P.O. Box 624 • Brenham, TX 77834  
800.231.0454

CRUNCH is a concentrated blend of organic solvents and easy to do. Continue rinsing. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If swallowed, immediately call a poison center/doctor. Do NOT induce vomiting. Dispose of contents/ container in accordance with local, state, and federal law.

**DIRECTIONS FOR USE:** When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar. **FOR ENGINES:** Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying. **OTHER SURFACES:** To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

**MODO DE EMPLEO:** Cuando se use en superficies pintadas, pruebe en un área pequeña para asegurar que la pintura no sea afectada. Sostenga el bote de 8 a 10 pulgadas del área que se va a rociar. Aplique una capa asegurándose de cubrir toda la grasa, aceite y alquitran. **PARA MOTORES:** Cubra la toma del carburador y el distribuidor con plástico o papel aluminio para evitar contaminación con agua. Permita que el producto actúen por 15 minutos para que ocurra una completa penetración y emulsificación. Limpie con manopla. Remueva el plástico o papel aluminio y encienda el motor por 15 minutos para que se seque bien. **OTRAS SUPERFICIES:** Para remover aceite, grasa, alquitran y asfalto de otras superficies, aplique sobre la superficie cubriendo el área que se va a limpiar. Permita que el producto trabale por 10 o 15 minutos. Lave con un fuerte chorro de agua. Áreas muy sucias pueden ser frotadas o un segunda aplicación.

**DANGER:** Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation and serious eye damage. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye/face protection and protective gloves if on skin. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Remove cautiously with water for several minutes. Remove contact lenses if present

**CONTAINS (CAS#):** Water (7732-18-5), Petroleum Distillates, hydrocarbonated light (64749-47-8), Nonoxynol (127087-87-0), Propane (74-98-6), Glycol Ether DPHB (29911-28-2).

For more ingredient information visit  
[www.questspecialty.com](http://www.questspecialty.com)

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A

NFPA  
FIRE HAZARD  
HEALTH HAZARD  
REACTIVITY  
SPECIAL



ITEM 825000001-20AR

Made in USA