

QuestSpecialty

**SURRENDER**

**Ultra High-Temp  
Anti-Seize**

**SURRENDER**

**Ultra High-Temp  
Anti-Seize**  
**Ultra Antigripante de  
Alta-Temperatura**

**Stops Corrosion**

**Withstands Extreme Pressure**

**Temperature Range of -30° to 2200°F**

**Decreases Seizure, Pitting,  
Galling & Thread Distortion**

**CAUTION/PRECAUCIÓN:**  
**KEEP OUT OF REACH OF CHILDREN**  
**SEE ADDITIONAL CAUTIONS ON BACK PANEL**  
**NO SE DEJE AL ALCANCE DE LOS NIÑOS**  
**VEA PRECAUCIONES ADICIONALES EN EL PANEL TRASERO**

**NET CONTENTS: 14 OZ. (397 g)**

QuestSpecialty Corporation  
P.O. Box 624 • Brenham, TX 77834  
713.896.8188

*Contains no lead or copper;  
Non-melting base.*

SURRENDER ANTI-SEIZE is three  
useful maintenance compounds  
in one:

1. A high temperature anti-seize compound from -30°F to +2200°F.
2. A high temperature anti-friction bearing and slide lubricant with high dropping point, extreme pressure high speed capabilities to 350°F and low-speed high temperature dry film lubrication to 1500°F (low RPM bearing applications only).
3. A protective coating for highly corrosive service in high temperature applications from -30°F to +1000°F.

It is well suited for service where water is a problem, is insoluble in polar solvents but miscible at room temperature with all hydrocarbon solvents.

**USES:**

**INDUSTRIAL:** For nuts, valves, flanges, studs, threaded fittings, bushings, manifold surfaces, plugs, valve shafts, valve assemblies, gaskets, bolts, conveyors, gear reducers, transmission shafts, fans, blowers, compressor pumps, turbines, etc.

**STATIONARY AND MARINE ENGINES:** Valve gauges and gaskets, fuel injectors, air starting valves, compressor gauges and piping, cylinder head gaskets and stud assemblies.

**TRUCK FLEETS:** Cylinder head assemblies, exhaust manifold

and turbo charger fittings, torque rod tubes and pins, brake anchor pins, air cylinder assemblies.

**DIRECTIONS FOR USE:** Pump in new product until old comes out. Remove old product if possible.

**MODO DE EMPLEO:** Inyecte producto nueva hasta que la vieja salga. Remueva la producto vieja si es posible.

**CAUTION:** Keep out of reach of children. Avoid contact with eyes and clothing.

**PRECAUCIÓN:** No se deje al alcance de los niños. Evite el contacto con ojos y ropa.

**CONTAINS (CAS#):** Hydrotreated Naphthenic Petroleum Distillate (64742-52-5), Aluminum (7429-90-5), Lithium Stearate (4485-12-5).

**NLGI GRADE: 2**

**HMIS Ratings:** Health - 1, Flammability - 1, Reactivity - 0, Personal - A.

Made in USA

600005056



ITEM L63900001-145G