



SURRENDER

Anti-Seize

SURRENDER

Anti-Seize / Antiagarre

**Stops Corrosion • Extreme Pressure & Heat Resistant
Decreases Seizure, Pitting, Galling & Thread Distortion**

**KEEP OUT OF REACH OF CHILDREN NO SE DEJE AL ALCANCE DE LOS NIÑOS
CAUTION PRECAUCION**

See Additional Cautions on Back Panel

Vea Precauciones Adicionales a Lado

NET WT. 1 LB.

SURRENDER has a non-melting base and is well suited for service where water is a problem. Insoluble in polar solvents, but miscible at room temperature with all hydrocarbon solvents.

SURRENDER ANTI-SEIZE is three useful maintenance compounds in one.

1. A high temperature anti-seize compound from -30°F to +2200°F.
2. A high temperature anti-friction bearing and slide lubricant capable of extreme pressure. High speed capabilities to 350°F and low-speed dry film lubrication to 1500°F (Low RPM bearing applications only).
3. A protective coating for highly corrosive service in high temperature applications from -30°F to +1000°F.

INDUSTRIAL: Nuts, valves, flanges, studs, threaded fittings, bushings, manifold surfaces, plugs, valve shafts, valve assemblies, gaskets, bolts, conveyors, gear reducers, transmission shafts, fans, blowers, compressor pumps, turbines, etc. **STATIONARY AND MARINE ENGINES:** Valve gauges and gaskets, fuel injectors, air starting valves, compressor gauges, and piping, cylinder head gaskets and stud assemblies.

TRUCK FLEETS: Cylinder head assemblies, exhaust manifold and turbo charger, fittings, torque rod tubes and pins, brake anchor pins, air cylinder assemblies.

CAUTION: Keep out of reach of children. Avoid contact with eyes and clothing.

PRECAUCION: No se deje al alcance de los niños. Evite el contacto con ojos y ropa.

WARNING: Cancer and birth defects or other reproductive harm - www.P65Warnings.ca.gov.

ADVERTENCIA: Cáncer y defectos de nacimiento u otros daños reproductivos - www.P65Warnings.ca.gov.

CONTAINS (CAS #): Distillates (petroleum), hydrotreated heavy naphthene (64742-52-5), Aluminum (7429-90-5), Graphite (7782-42-5), Amorphous silica (112945-52-5), Distillates (petroleum), hydrotreated light (64742-47-8).

HMS Ratings: Health - 1, Flammability - 1, Reactivity - 0, Personal - A.

QuestSpecialty Corporation
PO Box 624 • Brenham, TX 77834
800.231.0464 • www.questspecialty.com

ITEM L63900001-001G 600004639

