

Safety Data Sheet

Sleek

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Sleek
PRODUCT CODE: 2160
RECOMMENDED USE: Furniture Polish
RESTRICTIONS ON USE: None Known
COMPANY NAME: QuestSpecialty Corporation
COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834
COMPANY PHONE: 800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 2
Gases Under Pressure: Liquefied Gas
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: N/A

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Distillates (petroleum), hydrotreated light	64742-47-8	10-30%
Propane	74-98-6	1-5%
N-Butane	106-97-8	1-5%

SECTION IV - FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Oral: Aspiration risk

CHRONIC HEALTH HAZARDS: None known

NOTE TO PHYSICIAN: Treatment of overexposure should be directed toward the control of symptoms and the clinical condition.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical or suitable for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: N/A

Safety Data Sheet

Sleek

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Use non-combustible material like vermiculite, sand or earth on spill sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children and do not store near food, drink, or animal food.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Distillates (petroleum), hydrotreated light	Not Established	Not Established
Propane	1000 ppm	1000 ppm
N-Butane	Not Established	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation suitable, forced ventilation should not be required

RESPIRATORY PROTECTION: Not required with normal use.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses

ADDITIONAL MEASURES: Wash hands thoroughly after handling. Follow normal hygiene practices.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White aerosol.

ODOR: Lemon scent

ODOR THRESHOLD: N/D

pH: 6

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: > 212°F (100°C)

FLASH POINT: 134° F (56.7°C)

EVAPORATION RATE: N/D

FLAMMABILITY(solid/gas): Flammable Aerosol

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOISVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR=1): N/D

RELATIVE DENSITY (H2O=1): 0.940

SOLUBILITY(IES): 70%

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

Safety Data Sheet

Sleek

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: None known.

CHEMICAL STABILITY: Stable

POSSIBLE HAZARDOUS REACTIONS: None Known

CONDITIONS TO AVOID: None known

INCOMPATIBLE MATERIALS: Strong acids, strong alkalis, strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Distillates (petroleum), hydrotreated light** (64742-47-8) LD₅₀ (Oral, Rat) >5000 mg/kg; LD₅₀ (Dermal, Rabbit) >2000 mg/kg **Propane** (74-98-6) LC₅₀ (Inhalation, Rat, 4hr) 658 mg/l **n-Butane** (106-97-8) LC₅₀ (Inhalation, Rat, 4hr) 30957 mg/m³

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation.

INGESTION: May cause gastrointestinal irritation, nausea.

INHALATION: Irritant. Avoid breathing spray mist. May cause irritation to respiratory tract.

SKIN: May cause mild irritation, dryness with prolonged or repeated contact.

MEDICAL CONDITION AGGRAVATED: None known

ACUTE HEALTH HAZARDS: Oral: Aspiration risk

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Avoid release to the environment. **Distillates (petroleum), hydrotreated light** (64742-47-8) Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms.

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

Safety Data Sheet

Sleek

UN/NA NUMBER: UN 1950
PACKING GROUP: N/A
ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: None

SARA 313 REPORTABLE INGREDIENTS: None

CLEAN WATER ACT: None

STATE REGULATIONS: California Proposition 65: None

INTERNATIONAL REGULATIONS: All components are listed or exempted.

VOLATILE ORGANIC COMPOUNDS (VOC): 6.7%

NFPA HEALTH: 2

HMIS HEALTH: 2

NFPA FLAMMABILITY: 2

HMIS FLAMMABILITY: 2

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: None

HMIS PROTECTION: A

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Roberto Ceron

DATE PREPARED: 12/16/2013

REVISION DATE: 06/03/2021

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.