

Safety Data Sheet
Unplug

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Unplug
PRODUCT CODE: 6006
RECOMMENDED USE: Industrial Degreaser
RESTRICTIONS ON USE: None Known
COMPANY NAME: QuestSpecialty Corporation
COMPANY ADDRESS: P.O. Box 624, Brenham, TX 77834
COMPANY PHONE: 800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Liquid: Category 2
Skin Irritant: Category 2
Eye Irritant: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Highly flammable liquid and vapor. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Keep container tightly closed. Wear protective gloves and eye protection. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water or shower. If skin irritation occurs: Get medical advice or attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. In case of fire use dry chemical, foam, or carbon dioxide. Store in a well-ventilated place. Keep container tightly closed and cool. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Wash hands thoroughly after handling. Avoid breathing fumes, mist, or vapors. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

For large quantities: Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Heptane	142-82-5	60-100%
Isopropyl Alcohol	67-63-0	7-13%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Inhalation: dizziness, drowsiness, weakness, and fatigue

Eye: stinging, tearing, redness

Safety Data Sheet

Unplug

Oral: Aspiration risk

Skin: Prolonged or repeated contact may dry skin

CHRONIC HEALTH HAZARDS: Skin disorders, drying and irritation of the skin.

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers. Shut off all sources of ignition.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from heat/sparks/open flames/hot surfaces. No smoking. May develop a flammable atmosphere in confined areas.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Clean up with non-combustible material like vermiculite, sand or earth. If many cans are opened remove ignition sources. Prevent spill from entering sewers, storm drains, and natural waterways.

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Store in a well ventilated place. Keep cool. Wear protective gloves and eye protection.

OTHER PRECAUTIONS: Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warning and precautions listed for the product.

INCOMPATIBILITY: Oxidizers, heat, sparks, open flame, and energized equipment.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	400 ppm	400 ppm
Isopropyl Alcohol	400 ppm	200 ppm

ENGINEERING CONTROLS / VENTILATION: Use only in well ventilated areas. Forced ventilation required. Local exhaust preferred to general.

RESPIRATORY PROTECTION: Use only in well ventilated areas. If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear Liquid

ODOR: Alcohol solvent

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: N/D

FLASH POINT: N/D

EVAPORATION RATE: >2.5

Safety Data Sheet

Unplug

FLAMMABILITY(solid/gas): Highly Flammable Liquid
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:
LOWER FLAMMABILITY LIMIT: N/A
UPPER FLAMMABILITY LIMIT: N/A
EXPLOSIVE LIMIT LOWER (%): N/D
EXPLOSIVE LIMIT UPPER (%): N/D
VAPOR PRESSURE (mm Hg): 124 mmHg @ 75°F
VAPOR DENSITY (AIR=1): 4.5
RELATIVE DENSITY (H₂O=1): 0.69 - 0.725
SOLUBILITY(IES): 10%
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
AUTOIGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: If exposed to strong oxidizers, presents explosion hazard.
CHEMICAL STABILITY: Stable
POSSIBLE HAZARDOUS REACTIONS: None Known
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.
INCOMPATIBLE MATERIALS: Oxidizers, heat, sparks, open flame, and energized equipment.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Heptane (142-82-5) LC₅₀ (Vapors, Mice) 1600 ppm
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: Causes irritation, redness, tearing, pain, blurred vision.
INGESTION: May be harmful if swallowed. Not an expected route of exposure. Nausea, vomiting, headaches, abdominal pain, diarrhea, dizziness, pulmonary edems, unconsciousness or death
INHALATION: Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.
SKIN: Brief contact is not irritating. May cause irritation, dryness, redness, localized defatting with prolonged or repeated contact. Removes natural oils and fats from skin.
MEDICAL CONDITION AGGRAVATED: Asthma, bronchitis, emphysema and other lung diseases and chronic nose, sinus or throat conditions. Skin irritation may be aggravated in individuals with existing skin disorders.
ACUTE HEALTH HAZARDS: Inhalation: dizziness, drowsiness, weakness, and fatigue
Eye: stinging, tearing, redness
Oral: Aspiration risk
Skin: Prolonged or repeated contact may dry skin
CHRONIC HEALTH HAZARDS: Skin disorders, drying and irritation of the skin.
CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: No

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Isopropyl Alcohol (67-63-0) LC₅₀ (Fathead Minnow, 96 hrs) 9640 mg/L
PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.
MOBILITY IN SOIL: This product is mobile in soil.
OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.
RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet
Unplug

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Flammable Liquid, N.O.S., (Heptane, Isopropanol)
HAZARD CLASS/DIVISION: 3
UN/NA NUMBER: UN 1993
PACKING GROUP: II

AIR SHIPMENT

PROPER SHIPPING NAME: Flammable Liquid, N.O.S., (Heptane, Isopropanol)
HAZARD CLASS/DIVISION: 3
UN/NA NUMBER: UN 1993
PACKING GROUP: II

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Flammable Liquid, N.O.S., (Heptane, Isopropanol)
HAZARD CLASS/DIVISION: 3
UN/NA NUMBER: UN 1993
PACKING GROUP: II
ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: Acute Health, Fire

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: **Heptane** (142-82-5) California Director's List of Hazardous Substances, Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, New Jersey RTK, Massachusetts RTK, Minnesota RTK, Pennsylvania RTK, Rhode Island RTK

Isopropyl Alcohol (67-63-0) Right-to-Know acts for Rhode Island, Pennsylvania, Florida, Minnesota, Massachusetts, New Jersey, Tennessee Connecticut hazardous material survey. Isopropyl alcohol Illinois toxic substances disclosure to employee act

INTERNATIONAL REGULATIONS: All components are listed or exempted.

VOLATILE ORGANIC COMPOUNDS (VOC): 100%

NFPA HEALTH: 1
NFPA FLAMMABILITY: 3
NFPA REACTIVITY: 0
NFPA OTHER: None

HMIS HEALTH: 1
HMIS FLAMMABILITY: 3
HMIS REACTIVITY: 0
HMIS PROTECTION: B

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Andrew Bach

DATE PREPARED: 12/06/2013

REVISION DATE: 07/17/2019

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.