

MAXI GLO

LIGHT DUTY NEUTRAL CLEANER

DESCRIPTION

MAXI GLO is a USDA authorized, all purpose, light duty, non-butyl, neutral cleaner. Dilutes up to 128:1 with water. Cleans all surfaces including tile, terrazzo, porcelain, marble, concrete, wood, enamel and metal. Also for cleaning glass windows. Contains surfactants, emulsifiers and wetting agents to clean oil, grease, grime, dirt, inks and most other soils. Will not harm any surface not harmed by water. Excellent for mopping floors coated with wax or floor finish; will not remove or harm floor coatings.

APPLICATIONS

A perfect neutral cleaner to use on grease, grime, oil, dirt, mud, carbon, ink and soot. Areas of use include industrial plants, offices, stores, hotels/motels, schools, restaurants and apartments.

FEATURES & BENEFITS

- Economical—dilutes up to 128:1. Low end use cost per gallon.
- · Safe. Designed to complement the technology of today's high gloss floors. Will not dull even the glossiest finishes.
- · Effective in hard water.
- Pleasant cherry fragrance.

SPECIFICATIONS

FORM: Liquid
ODOR: Cherry
COLOR: Red Amber
DETERGENCY: Mild
TOXICITY: Non-hazardous
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: <2%

FLASH POINT: Not Tested BOILING POINT: 212°F + SOLUBILITY IN WATER: 100% SPECIFIC GRAVITY: 1.01 % VOLATILE BY VOLUME: 85% +

pH: 9.5

VISCOSITY: Thick

EVAPORATION RATE: Slow BIODEGRADABILITY: Yes

LABEL INFORMATION

MAXI GLO

LIGHT DUTY NEUTRAL CLEANER

MAXI GLO is a light duty cleaner and degreaser for use on floors, walls, tile, terrazzo, concrete, woodwork, enamel, porcelain, windows and metal surfaces. Use full strength for tough cleaning jobs or dilute as directed for general purpose cleaning. Removes grease, grime, oil, food stains, dirt, lipstick, black heel marks, carbon, soot and soap scum. Biodegradable in hard or soft water.

DIRECTIONS FOR USE

COMPOSITION, TERRAZZO, TILE and MARBLE FLOORS: Add 2 oz. to each gallon of warm water. Mop floor with solution, remove with squeegee or damp mop. For optimum floor coating application, rinse with clear water. For regular floor maintenance, no rinsing is required. WOOD and CONCRETE FLOORS: Add 1 cup to each gallon of warm water. Scrub surface, rinse with clear water. WALLS, WOODWORK, PORCELAIN, ENAMEL and METAL SURFACES: Add 4 oz. to each gallon of water. WINDOWS: Add 1 oz. to each 2 gallons of water. Apply with soft brush, remove with squeegee.

WARNING: Causes eye irritation.

Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

CONTAINS (CAS#): Water (7732-18-5), Tall Oil Fatty Acid (61790-12-3), Sodium Tripolyphosphate (7758-29-4), Nonionic Surfactant (68439-46-3).

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	Α



PACKAGING INFORMATION

Available in 4 x 1 gallons, 5 and 6 gallon pails and 55 gallon drums.