

QUIK SOLV

SOLVENT DEGREASER



DESCRIPTION

QUIK SOLV replaces chlorinated solvent degreasers, providing industry with an excellent solvent on oils, greases, waxes, resins, epoxies, polymers, and more. QUIK SOLV is non-flammable, fast-drying, non-conductive and leaves no residue. Cleans most metals including aluminum, magnesium, copper, brass, tin plate and more without dulling, corroding, oxidizing or staining. Safe on most plastics used in contact and circuit board construction. If unsure of compatibility, test in an inconspicuous area prior to use. Due to VOC regulations, not available for sale in CA, CT, MD, PA, NJ, OH, MA, ME, MI, NY, DE, VA, DC, NH, UT.

APPLICATIONS

For use on electric motors, power tools, printing presses, refrigeration and air conditioning equipment, generators and starters, office machines, ultrasonic cleaners, film cleaning equipment and other machinery. Areas of use include auto repair shops, factories, printers, machine shops, aircraft services, HVAC services, and electrical maintenance services.

FEATURES & BENEFITS

- High solvent power
- Non-flammable
- Non-conductive
- Non-chlorinated

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Strong Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: N/A
WETTING ABILITY: Moderate
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: N/A
SOLUBILITY IN WATER: Non-soluble
SPECIFIC GRAVITY: 1.3
% VOC: 97%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

QUIK SOLV SOLVENT DEGREASER

QUIK SOLV provides industry an alternative to products containing chlorinated solvents. Dries quickly, leaving no residue. The low-odor, non-flammable, non-conductive formula cleans and degreases electric motors, power tools, printing presses, refrigeration and air conditioning equipment, generators and starters, office machines, most metals including steel, nickel, zinc, titanium, galvanized steel, copper, magnesium, brass and tin plate. Also safe for use on some plastics, including those used in contact and circuit board construction. May affect certain types of plastics, such as PVC, ABS, acrylic styrenes, and polycarbonates. If unsure of compatibility, test in an inconspicuous area prior to use.

DIRECTIONS FOR USE: Spray surface to be cleaned and wipe with clean cloth. For heavy deposits, let stand for 30 seconds or scrub with brush. Flush a second time and wipe with clean cloth. Electric motors may be cleaned while in operation. Blow dry with compressed air and lubricate bearings after cleaning.

DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May damage fertility or the unborn child. May cause respiratory irritation, drowsiness, or dizziness. Suspected of causing cancer. Presumed to have the potential to produce significant nervous system toxicity in humans through prolonged or repeated exposure. May be harmful if swallowed. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Wash hands thoroughly after handling, take off contaminated clothing and wash it before reuse. Wear chemical resistant gloves of Viton or Silvershield material and safety glasses. If on skin, wash with plenty of water. If skin irritation occurs, get medical advice or attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice/attention. Keep container tightly closed. Store in a well-ventilated place. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor and get medical attention if you feel unwell. Do not eat, drink or smoke when using this product. If swallowed: Immediately call a poison center/doctor. Rinse mouth. Dispose of contents and container in accordance with local/regional/national regulations.

 **WARNING:** Cancer and birth defects or other reproductive harm - www.P65Warnings.ca.gov.

CONTAINS (CAS#): n-Propyl Bromide (106-94-5), Carbon Dioxide (124-38-9).

PACKAGING INFORMATION

12 – 20 oz. cans per case, 20 oz. net weight

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B

NFPA		FIRE HAZARD	
HEALTH HAZARD	2	1	0
		REACTIVITY	
		SPECIAL	