

LEFT HOOK

ELECTRONIC CLEANER



DESCRIPTION

LEFT HOOK is a high purity, high dielectric, rapidly evaporating, non-flammable spray specially formulated for removing oil, grease, condensation and other contaminants from sophisticated electronic parts. Ideal for removing grease and dirt from sensitive electronics, televisions and telephone equipment.

*Quick drying formula will not harm Neoprene, Buna, Silicone, Butyl, Natural Rubber, Hypalon, PTFE, Styrene, Polystyrene, Polyethylene, Polypropylene, Epoxy, ABS, Nylon, PVC and Polyurethane.

APPLICATIONS

For use on circuit boards, terminals, relays, switches, contacts, circuit breakers, tuners, control panels, motors and other electronic equipment.

FEATURES & BENEFITS

- No Citrus Oil
- Fast Drying
- Safe on Most Plastics*, Paints, Rubber & Electronic Insulation
- Non-Flammable
- Residue Free
- Low Odor

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Halogenated Solvent
COLOR: Clear, Colorless
DETERGENCY: Excellent
TOXICITY: 200 PPM OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 year
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/D
FLAME EXTENSION: None
SOLUBILITY IN WATER: Non-Soluble
SPECIFIC GRAVITY: 1.285
% VOC: 20.2%
pH: N/A
PROPELLANT: 134a
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

LEFT HOOK ELECTRONIC CLEANER

LEFT HOOK is a high purity, high dielectric, rapidly evaporating, non-flammable spray specially formulated for removing oil, grease, condensation and other contaminants from sophisticated electronic parts. Ideal for removing grease and dirt from sensitive electronics, televisions and telephone equipment.

*Quick drying formula will not harm Neoprene, Buna, Silicone, Butyl, Natural Rubber, Hypalon, PTFE, Styrene, Polystyrene, Polyethylene, Polypropylene, Epoxy, ABS, Nylon, PVC and Polyurethane.

FOR USE ON: Circuit boards, terminals, relays, switches, contacts, circuit breakers, tuners, control panels, motors and other electronic equipment.

DIRECTIONS FOR USE: Spray directly onto surface, holding can close to work. For hard to reach areas, insert extension tube into actuator orifice. Allow components to dry completely before applying current.


DANGER: Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause respiratory irritation, drowsiness or dizziness. May cause damage to the central and peripheral nervous systems, brain, lungs kidneys and reproductive system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, protective clothing and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe the mist, vapors, or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do not induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

WARNING: Birth defects or other reproductive harm - www.P65Warnings.ca.gov

CONTAINS (CAS#): 1,1,2,2-Tetrafluoroethyl 2,2,2-Trifluoroethyl Ether (406-78-0), 1,1,1,2-Tetrafluoroethane (811-97-2), Trans, 1,2 Dichloroethylene (156-60-5), Ethyl Alcohol (64-17-5), Hexane (110-54-3).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz. cans per case, 10 oz. net weight