

# LINK WISE

## FOOD GRADE SEMI-SYNTHETIC CHAIN LUBE



### DESCRIPTION

**LINK WISE** combines synthetic lubricants and mineral oil into a formula that penetrates, lubricates and protects roller drive and conveyor chains. Deep penetrating foam reduces friction and wear on all types of chains and conveyors operating in food processing areas. NSF H1 rated for incidental food contact.

### APPLICATIONS

Excellent for use on conveyor chains, packaging equipment, food service carts, sliding tracks, filling equipment, food racks, channels, open drives, hoist chains, link and roller assemblies, forklift trucks and many other industrial applications.

### FEATURES & BENEFITS

- Temperature range 0°F - 325°F
- Tacky formula resists sling-off & water washout
- High flash point
- For all types of chains and conveyors operating in food contact areas

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol  
**ODOR:** Bland  
**COLOR:** Viscous Yellow  
**DETERGENCY:** None  
**TOXICITY:** 400 ppm OSHA TLV  
**WETTING ABILITY:** None  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** N/A  
**FLAME EXTENSION:** 18" +  
**SOLUBILITY IN WATER:** None  
**SPECIFIC GRAVITY:** 0.883  
**% VOLATILE BY VOLUME:** 0%  
**pH:** N/A  
**PROPELLANT:** Hydrocarbon  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

**LINK WISE**  
**FOOD GRADE SEMI-SYNTHETIC CHAIN LUBE**

**LINK WISE** combines synthetic lubricants and mineral oil into a formula that penetrates, lubricates and protects roller drive and conveyor chains. Deep penetrating foam reduces friction and wear on all types of chains and conveyors operating in food processing areas. NSF H1 rated for incidental food contact.


**FOR USE ON:** Conveyor chains, packaging equipment, food service carts, sliding tracks, filling equipment, food racks, channels, open drives, hoist chains, link and roller assemblies, forklift trucks and many other industrial applications.

**DIRECTIONS FOR USE:** Shake well. Remove protective cap and point spray opening in desired direction. Holding container 6-12 inches from surface to be treated, spray product liberally, saturating parts. For extremely difficult jobs, saturate and allow to set 5-10 minutes. Repeat periodically.

**DANGER:** Flammable Aerosol. Contains gas under pressure; May explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. If swallowed: Immediately call a poison center or a doctor. Do NOT induce vomiting. Dispose of contents/container in accordance with local, regional and national guidelines.

**CONTAINS (CAS#):** Mineral Oil (8042-47-5), Propane/n-Butane (68476-86-8), Polybutene (9003-29-6).

|              |   |
|--------------|---|
| HEALTH       | 2 |
| FLAMMABILITY | 2 |
| REACTIVITY   | 1 |
| PERSONAL     | A |



### PACKAGING INFORMATION

12 – 16 oz. cans per case, 12 oz. net weight