

# AQUA-LUB

## LUBRICANT



### DESCRIPTION

**AQUA-LUB** is a USDA authorized lubricating product. Formulated to quickly penetrate rust, corrosion and moisture. Lubricates, cleans and contains rust preventative. Non-flammable and non-conductive to 29,000 volts. Four-way action cleans, lubricates, prevents rust and penetrates. Due to VOC regulations, not available for sale in California and Utah.

### APPLICATIONS

For use on motors, wire cable, rusted parts, ignition systems, machine parts, door hinges, locks, nuts and bolts and refrigeration equipment. Areas of use include homes, hotels/motels, airplanes, cars and trucks, machine shops, oil rigs, manufacturing facilities, industrial plants and factories.

### FEATURES & BENEFITS

- Versatile light duty formula penetrates, lubricates, prevents corrosion and displaces moisture
- Silicone free formula will not interfere with subsequent painting
- Non-flammable
- Meets MIL Spec C-2344

### SPECIFICATIONS

**FORM:** Solvent-Based Aerosol  
**ODOR:** Chlorinated Solvent  
**COLOR:** Brown  
**DETERGENCY:** None  
**TOXICITY:** 25 ppm OSHA PEL  
**WETTING ABILITY:** Saturates  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 0°F  
**PHOSPHATES:** None

**FLASH POINT:** N/A  
**FLAME EXTENSION:** None  
**SOLUBILITY IN WATER:** 0%  
**SPECIFIC GRAVITY:** 1.365  
**% VOC:** 42.7%  
**pH:** N/A  
**PROPELLANT:** Carbon Dioxide  
**EVAPORATION RATE:** Medium  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### AQUA-LUB LUBRICANT

**AQUA-LUB** is a powerful, multiple-action protective shield against the harmful effects of moisture and corrosion. Loosens dirt and scale from corroded threads, tightly fitted parts, sliding and rotating parts, bolts, hinges and pins which have been "frozen" by corrosion. It protects electrical gear, metal and other surfaces from deterioration by displacing water and moisture and sealing all surfaces with a complete molecular film. It preserves equipment, reducing repair and maintenance costs. Never becomes dry, brittle or hard. Can be used on dry or wet surfaces.

**Contains a rust preventative that will protect against renewed corrosion**


**DIRECTIONS:** Spray liberally directly on area to be treated. Reapply periodically as required.

**DANGER:** Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. Suspected of causing genetic defects. May cause cancer. May cause drowsiness or dizziness. May cause an allergic skin reaction. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection, and protective clothing. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.

**⚠ WARNING:** Cancer and birth defects or other reproductive harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**CONTAINS (CAS#):** Trichloroethylene (79-01-6), Tetrachloroethylene (127-18-4), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Carbon dioxide (124-38-9), Petrolatum (petroleum), oxidized, calcium salts (68425-34-3).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



### PACKAGING INFORMATION

12 – 16 oz. cans per case, 16 oz. net weight