

Technical Data Report

RUTHLESS

PAINT REMOVER


DESCRIPTION

RUTHLESS is a USDA authorized gel base paint remover. Penetrates deep to remove paint, epoxy paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials from all surfaces. Washes off with water or solvent. Safe to use on metal, brick, ceramic, wood and tile surfaces. Clings to all vertical surfaces.

APPLICATIONS

Works hard to remove paint, epoxy, lacquer, carbon deposits and silicone. Areas of use include auto dealers, paint shops, factories, schools, farms, oil rigs, bottling plants, lumber mills and cement plants.

FEATURES & BENEFITS

- Gel based formula clings to vertical surfaces, allowing longer contact time
- Removes a wide range of paints and surface sealers from metal, concrete and wood
- Ease of use—simply spray on and wipe or rinse

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: Excellent
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: N/A

FLASH POINT: N/A
FLAME EXTENSION: None
SOLUBILITY IN WATER: 14%
SPECIFIC GRAVITY: 1.185
% VOLATILE BY VOLUME: 98%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Medium
BIODEGRADABILITY: No

LABEL INFORMATION
RUTHLESS
PAINT REMOVER

Gel formulation paint remover quickly removes paint, epoxy paint, lacquer, shellac, enamel, varnish, labels, carbon deposits, silicone, simulated wood paneling and similar materials. Product will not run. This formula has been authorized by the USDA for use in federally inspected meat and poultry plants.

For use by auto dealers, paint shops, maintenance departments, engine rebuilders, factories, furniture refinishers, painters, sign builders, schools, motels, hotels, hospitals and offices. For use on metal parts, plaster, concrete, tile, glass, ceramic, engine parts, valve seals, paint guns, paper, wood, stone, masonry and cylinders.

DIRECTIONS: Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

CAUTION: Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to health depends on level and duration of exposure.


DANGER: Flammable Aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin and eye irritation. Suspected of causing cancer. Causes damage to eyes or central nervous system with prolonged or repeated exposure.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Call a poison center or doctor if you feel unwell. Rinse mouth. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Do not breathe fumes, mist, vapors, or spray.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Methylene Chloride (75-09-2), Propane/n-Butane (68476-86-8), Methanol (67-56-1), Methylcellulose (9004-65-3), Petroleum Wax (64742-43-4).

HEALTH	3
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B


PACKAGING INFORMATION

5580: 12 – 16 oz. cans per case, 13 oz. net weight

5590: 12 – 20 oz. cans per case, 18 oz. net weight (Private Label Only)