

NO SPAT

ANTI-SPATTER



DESCRIPTION

NO SPAT anti-spatter prevents sticking of slag and spatter on metal surfaces. Contains no silicone which can weaken welds and prevent paint from adhering to welded surfaces. Leaves surface paintable once rinsed with water. Quickly evaporates. Contains a non-flammable solvent carrier for extra safety. Prolongs life of welding parts and equipment.

APPLICATIONS

Used for welded parts, fixtures and MIG gun nozzles and tips. Areas of use include welding shops, industrial plants, automotive shops.

FEATURES & BENEFITS

- Contains no silicone, allowing paint to adhere to welded surfaces after rinsing
- Keeps welding nozzles clean
- Prolongs life of gun nozzles, contact tips, welded parts and fixtures
- Prevents sticking

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Amyl Acetate and Solvent
COLOR: Clear
DETERGENCY: Mild
TOXICITY: 50 ppm OSHA TLV
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: None
FLAME EXTENSION: None
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.38
% VOLATILE BY VOLUME: 90%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Fast
BIODEGRADABILITY: Yes

LABEL INFORMATION

NO SPAT ANTI SPATTER

This product is designed to be used on MIG gun nozzles, contact tips, welded parts and fixtures. Provides cleaner welds on fixtures and parts by reducing spatter. This product contains no silicone and is paintable after rinsing.


DIRECTIONS: Shake well before using. Clean existing spatter from tips and nozzles prior to use. Remove cap. Point spray opening in desired direction. Press button to spray. Hold container 4-6 inches from surface. Apply every 4 hours or as needed. Coat inside and outside of nozzles. Spray all surfaces or fixtures in close proximity to weld. Surfaces to be painted should be rinsed with water prior to paint application.

DANGER: Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May cause cancer. May cause drowsiness or dizziness. Suspected of causing genetic defects. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell

WARNING: This product can expose you to chemicals including Trichloroethylene, which is known to the State of California to cause cancer, birth defects or other reproductive harm.. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Trichloroethylene (79-01-6), Linoleic Acid (60-33-3), Carbon Dioxide (124-38-9), N-Amyl Acetate (628-63-7).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz cans per case, 16 oz net weight.