

Technical Data Report

BIG RED

NON-MELT SPRAY GREASE



DESCRIPTION

BIG RED is a cured lubricant that withstands heat to 350°F, moisture, acids, high pressure and is highly rust resistant. This 50 state VOC compliant formula provides superior lubrication while forming a thick, long-lasting film to prevent future corrosion. A high pressure additive reduces wear and prolongs operational life of all machinery. Temperatures above 350°F may require periodic reapplication.

APPLICATIONS

This lubricant is great for use on chains, winches, conveyors, gears, cables, tools, hinges, bushings, pins, levers and rollers. For use in all areas of industrial maintenance.

FEATURES & BENEFITS

- Waterproof and prevents corrosion
- Provides superior lubrication
- 0°F – 350°F temperature range
- Forms a thick, long-lasting film
- Red color provides easy visual inspection
- Accepts high pressure
- Prevents rust—extends life of equipment
- VOC compliant in all 50 states

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Solvent
COLOR: Opaque Red
DETERGENCY: None
TOXICITY: 500 ppm (TWA)
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: N/A
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: .850
% VOC: 79%
pH: N/A
VISCOSITY: Thin
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

BIG RED NON-MELT SPRAY GREASE

BIG RED is a cured lubricant that withstands heat to 350°F, moisture, acids, high pressure and is highly rust resistant. This 50 state VOC compliant formula provides superior lubrication while forming a thick, long-lasting film to prevent future corrosion. A high pressure additive reduces wear and prolongs operational life of all machinery. Temperatures above 350°F may require periodic reapplication. Use on chains, winches, conveyors, gears, cables, tools, hinges, bushings, pins, levers and rollers.

DIRECTIONS: Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. Use only outdoors or in a well-ventilated area. Avoid breathing fumes, vapors and sprays. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

CONTAINS (CAS#): • Heptane (142-82-5), Mineral oil (Mixture), Propane (74-98-6), Butane (106-97-8), trans-1,2- Dichloroethylene (156-60-5).

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 20 oz. cans per case, 14 oz. net weight