

ULTRA TAC

HIGH PRESSURE PENETRATING LUBRICANT



DESCRIPTION

ULTRA TAC is especially formulated to dispense as an oil-like lubricant designed to penetrate and lubricate. ULTRA TAC then sets up as a viscous, high impact grease, adding protection and heavy lubrication to the treated area. The unique formula contains PTFE which remains on surface, leaving a protective coating between lubrication periods.

APPLICATIONS

For use in garages, machine shops, industrial plants, construction sites, oil rigs, electronic repair shops, marinas and automotive repair shops.

FEATURES & BENEFITS

- Quickly penetrates rust, corrosion, and soil
- Excellent lubricant for gears, chains, slides, and turning parts
- Leaves a protective PTFE coating to protect tools and machinery to prolong their life

SPECIFICATIONS

FORM: Solvent-Based Aerosol
 ODOR: Solvent
 COLOR: Hazy/Tan
 DETERGENCY: N/A
 TOXICITY: None
 WETTING ABILITY: None
 STORAGE STABILITY: 1 Year +
 COLD STABILITY: 32°F
 PHOSPHATES: None

FLASH POINT: N/A
 FLAME EXTENSION: 18"
 SOLUBILITY IN WATER: 0.00%
 SPECIFIC GRAVITY: 0.795
 % VOLATILE BY VOLUME: 40%
 pH: N/A
 PROPELLANT: Hydrocarbon
 EVAPORATION RATE: Slow
 BIODEGRADABILITY: No

LABEL INFORMATION

ULTRA TAC HIGH PRESSURE PENETRATING LUBRICANT

Especially formulated to dispense as an oil-like lubricant designed to penetrate and lubricate. ULTRA TAC then sets up as a viscous, high impact grease adding protection and heavy lubrication to the treated area. The unique formula contains PTFE which remains on surface leaving a protective coating between lubrication periods.

SUGGESTED USES:

- Cables / Chains
- Hinges
- Gears
- Overhead Doors
- Sprockets / Winches


DIRECTIONS FOR USE: Shake well before using. Remove protective cap and point spray tip opening in desired direction. Saturate area to be lubricated. Insert extension tube in tip opening for hard to reach areas.

DANGER: Flammable Aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause respiratory irritation.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Petrolatum (8009-03-8), Propane/n-Butane (68476-86-8), Heptane (142-82-5), Petroleum distillates, hydrotreated light (64742-47-8), Petroleum Product Additive (N/A).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 20 oz. cans per case, 14 oz. net weight