

LOOSE SCREW

4-IN-1 LUBRICATING AND PENETRATING OIL WITH PTFE



DESCRIPTION

LOOSE SCREW is a non-flammable, 4-in-1 formula that penetrates, lubricates, displaces moisture and resists corrosion. This lubricant is used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, airlines, air maintenance shops and general industries. Contains no ozone depleters.

APPLICATIONS

This product excels as a: **Lubricant:** Superior, long-lasting lubricant made specifically to hold contact with metal, rubber, metal to rubber, or rubber to rubber contact. Fortified with ultra-slick PTFE which lowers inter-surface friction and increase lubricity. **Penetrant:** Penetrates frozen or rusted-on nuts, bolts, joints, couplings, pipe threads, or other parts and frees them for use. **Water Displacer:** Displaces water and moisture from electric contacts, mechanical controllers, machinery parts, equipment and many other water sensitive surfaces, keeping them functioning to peak efficiency. **Corrosion Inhibitor:** Adds a protective layer onto the surface to provide a physical barrier to water and oxygen to control corrosion on a variety of surfaces.

FEATURES & BENEFITS

- Non-Flammable
- 4-in-1 Lubricating & Penetrating Oil
- Displaces Moisture
- Contains PTFE to Increase Lubricity
- Inhibits Rust & Corrosion

SPECIFICATIONS

FORM: Solvent-Based Liquid
ODOR: Chlorinated Solvent
COLOR: Colorless
DETERGENCY:
TOXICITY:
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year
COLD STABILITY: 0°F
PHOSPHATES:

FLASH POINT: N/A
FLAME EXTENSION: N/A
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.365
% VOLATILE BY VOLUME: 100%
pH: N/A
VISCOSITY: N/A
EVAPORATION RATE:
BIODEGRADABILITY:

LABEL INFORMATION

LOOSE SCREW

4-IN-1 LUBRICATING AND PENETRATING OIL WITH PTFE

LOOSE SCREW is a non-flammable, 4-in-1 formula that penetrates, lubricates, displaces moisture and resists corrosion. This lubricant is used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, airlines, air maintenance shops and general industries. Contains no ozone depleters.

LOOSE SCREW excels as a: **Lubricant:** Superior, long-lasting lubricant made specifically to hold contact with metal, rubber, metal to rubber, or rubber to rubber contact. Fortified with ultra-slick PTFE which lowers inter-surface friction and increase lubricity. **Penetrant:** Penetrates frozen or rusted-on nuts, bolts, joints, couplings, pipe threads, or other parts and frees them for use. **Water Displacer:** Displaces water and moisture from electric contacts, mechanical controllers, machinery parts, equipment and many other water sensitive surfaces, keeping them functioning to peak efficiency. **Corrosion Inhibitor:** Adds a protective layer onto the surface to provide a physical barrier to water and oxygen to control corrosion on a variety of surfaces.


DIRECTIONS: Shake/stir contents to insure product uniformity prior to use. Spray/apply liberally until all moisture is rinsed away. This will also leave a protective coating to repel moisture. Repeat as needed. Can also be used to loosen rusty nuts and bolts.

DANGER: Causes skin and serious eye irritation. May cause drowsiness or dizziness. May cause cancer. Suspected of causing genetic defects. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local and national regulations. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Warning: This product contains a chemical(s) known to the State of California to cause cancer.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Petroleum Distillate (8052-41-3), Trichloroethylene (79-01-6), Mineral Oil (8042-47-5).

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

Available in 5 gallon pails and 55 gallon drums. Private label only.