

LIGHTNING

NONAMMONIATED WAX STRIPPER



DESCRIPTION

LIGHTNING is a highly concentrated non-ammoniated wax stripper. Removes all types of floor waxes, synthetic finishes, acrylics and latex finishes. Safe for use on most floor types. Not for use on wood or laminate floors. Contains strong wetting agents which penetrate to strip floors quickly and safely. Low sudsing and odorless. Non-flammable.

APPLICATIONS

To remove wax and wax buildup. Also removes dirt, grease, rubber marks and scuff marks. Areas of use include office buildings, hospitals, child care centers, nursing homes, schools, bank buildings, and supermarkets. Not for use on wood or laminate flooring.

NOTE: Resilient tile floors can be damaged by prolonged flooding with stripper. Do not flood tile floors.

FEATURES & BENEFITS

- Economical—dilution ratio of between 1:20 for lighter jobs to 1:4 for hard wax coats
- Convenient, fast drying and easy to apply
- Does not contain ammonia which can irritate eyes and skin
- Rinses easily with a wet vac or mop

SPECIFICATIONS

FORM: Liquid	FLASH POINT: N/A
ODOR: Mild sweet	BOILING POINT: 212°F
COLOR: Amber	SOLUBILITY IN WATER: 100%
DETERGENCY: Strong	SPECIFIC GRAVITY: 1.09
TOXICITY: 500ppm OSHA TLV	% VOLATILE BY VOLUME: >92%
WETTING ABILITY: Excellent	pH: 12.5
STORAGE STABILITY: 1 year +	VISCOSITY: Thin
COLD STABILITY: 32° F	EVAPORATION RATE: Slow
PHOSPHATES: Less than 2%	BIODEGRADABILITY: Yes

LABEL INFORMATION

LIGHTNING NONAMMONIATED WAX STRIPPER

This product is a concentrated heavy duty non-ammoniated wax stripper. For use on terrazzo, concrete and tile floors. Do not use on wood or cork floors. Strips off all wax and polymer finishes, low foaming characteristics make this product ideal for use with automatic floor machines as well as wet mopping. Removes stains, black heel marks, and rubber burns while stripping.

DIRECTIONS FOR USE: DO NOT USE ON WOOD OR CORK FLOORS. May affect pigments of low grade asphalt tile if used at stronger concentrations than 1 to 12. Test on small area of asphalt tile prior to use. Mix 1 part stripper to 20 parts hot water. For extra hard films, use 1 part stripper to 4 parts hot water. Apply solution and allow 10 minutes for penetration. Scrub with stripping pad.


NOTE: Resilient tile floors can be damaged by prolonged flooding with stripper. Do not flood tile floors.

WARNING: Causes skin and serious eye irritation.

Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

CONTAINS (CAS#): Water (7732-18-5), Sodium metasilicate pentahydrate (6834-92-0), Dipropylene glycol monomethyl ether (34590-94-8), Monoethanolamine (141-43-5), Sodium bicarbonate (144-55-8).

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

Available in 4 x 1 gallons, 5 and 6 gallon pails and 55 gallon drums.