

PRO-KOTE

SUPER HIGH GLOSS FLOOR POLISH

DESCRIPTION

PRO-KOTE is an extra high solids floor polish for use in heavy traffic areas. Designed for use in all types of maintenance programs. Non-yellowing, black mark resistant, fast drying and long wearing.

APPLICATIONS

For use on vinyl, terrazzo, stone and vinyl composition.

FEATURES & BENEFITS

- Excellent gloss
- Superior durability
- High solids
- Exquisite shine

SPECIFICATIONS

FORM: Liquid	FLASH POINT: None
ODOR: Bland	BOILING POINT: >212°F
COLOR: White	SOLUBILITY IN WATER: 100%
DETERGENCY: N/A	SPECIFIC GRAVITY: 1.03
TOXICITY: Non-hazardous	% VOLATILE BY VOLUME: 36%
WETTING ABILITY: Excellent	pH: 8.3
STORAGE STABILITY: 1 year +	VISCOSITY: Thin
COLD STABILITY: 32°F	EVAPORATION RATE: Slow
PHOSPHATES: >0.3%	BIODEGRADABILITY: No

LABEL INFORMATION

PRO-KOTE SUPER HIGH GLOSS FLOOR POLISH

PRO-KOTE has excellent anti-slip qualities. Coverage will vary depending on the age and type of floor from 1000 sq ft per gallon on the first coat, to 2500 sq. ft. on succeeding coats.


DIRECTIONS FOR USE: Prepare the floor carefully. Proper preparation will assure the finest appearance consistent with the time and materials invested. Remove all the old floor wax/finish with a heavy duty stripper, pad and machine. Rinse with clear water. Apply 1 coat of sealer/undercoater and allow to dry 45 minutes. Apply 2 coats of Pro-Kote allowing 20-30 minutes between coats. If no sealer/undercoater is used, apply 3-4 coats of Pro-Kote. Do not buff for 24 hours. For extra gloss and wear, allow floor to dry overnight, then apply two additional coats.

MAINTENANCE: Dust mop and spot mop daily to remove dust and spills. Use a neutral ph cleaner. Spray buff with soft pad or use a mop on dressing and high speed machine. Keep from freezing.

CAUTION: Keep out of reach of children. May be harmful if taken internally. Avoid contact with eyes. In case of contact, flush eyes with water for 15 minutes. Consult physician immediately.

CONTAINS (CAS#): Water (7732-18-5), Polystyrene/acrylic polymers (N/A), Diethylene glycol monoethyl ether (111-90-0), Wax emulsion (N/A).

HEALTH	0
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	A



PACKAGING INFORMATION

Available in 4x1 gallons, 5 and 6 gallon pails, and 55 gallon drums.