

DEEP GLOSS 18

FLOOR FINISH ACRYLIC, METAL CROSS LINK, HIGH GLOSS, 18% SOLIDS

DESCRIPTION

DEEP GLOSS 18 is a USDA authorized high solids formula that can be scrubbed daily with high speed automatic floor maintenance equipment without damage or dulling. This floor finish resists black marks, is extremely bright and levels well. Applications of 2,000 square feet per gallon in even, thin coats show the best results. Consists of metal cross linked acrylic polymers and polyethylene.

APPLICATIONS

For use on vinyl tile, rubber, cork, sealed wood, marble, concrete, terrazzo, brick and all resilient floors. Areas of use include hotels/motels, office buildings, homes, schools, stores, restaurants, banks, shopping malls, warehouses and factories.

FEATURES & BENEFITS

- · Durable finish is long lasting and scuff resistant
- · Levels with no streaks or mop trails
- · High coverage: one gallon yields up to 2,000 square feet of coverage

SPECIFICATIONS

FORM: Liquid
ODOR: Mild Ammonia
COLOR: White
DETERGENCY: N/A
TOXICITY: Nonhazardous
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 year +

COLD STABILITY: 32°F PHOSPHATES: N/A

FLASH POINT: None BOILING POINT: >212°F SOLUBILITY IN WATER: 100% SPECIFIC GRAVITY: 1.03 % VOLATILE BY VOLUME: 75%

pH: 8.4 VISCOSITY: Thin

EVAPORATION RATE: Slow BIODEGRADABILITY: No

LABEL INFORMATION

DEEP GLOSS 18 FLOOR FINISH

This product is a high solids, high gloss polymer floor finish. Once applied, it provides exceptional shine and protection to all types of tile and synthetic floors. Prevents black heel and rubber burn marks. Easy to maintain, just mop and allow to dry. Can be buffed if desired. Applies quickly and easily with damp mopping.

DIRECTIONS FOR USE: Strip off old floor finish thoroughly and rinse completely with water. Allow floor to dry. Apply thin even coats at a rate of 2000 square foot per gallon. Allow each coat to dry for 20 minutes before reapplying. Sweep floor and mop daily for best results. May be spray buffed if desired.

CAUTION: Do not take internally. If swallowed give water and contact physician. Keep out of eyes. If in eyes flush thoroughly with water and consult a physician.

CONTAINS (CAS#): Water (7732-18-5), Styrene-Acrylic Polymers (N/A), Diethylene Glycol monoethylether (111-90-0).

HEAL	TH	0
FLAMMABILITY		0
REACTIVITY		0
PERS	ONAL	Α



PACKAGING INFORMATION

Available in 4x1 gallons, 5 and 6 gallon pails, and 55 gallon drums.