



PAD-KLEEN







DESCRIPTION

PAD-KLEEN removes grease and tough grime from brake parts, linings and pads. Dries extremely fast and clean without residue. Nonflammable formula. Formulated to quickly and effectively remove grease, brake dust, brake fluids, oils and other contaminants. Cleans your brakes of build-up helping extend the life of your vehicle, while improving performance and keeping drivers safe. Due to VOC regulations, not available for sale in CA, NJ.

APPLICATIONS

For refrigeration and air conditioning units and parts, engines of all types, large and small electrical motors, outboard motors, magnetos, generators, electrical equipment and contacts, kitchen exhaust fans and vents, small power and hand tools, and brake parts.

FEATURES & BENEFITS

- BEST CLEANING FOR BRAKE PARTS!
- · Extremely fast-drying
- · Dissolves grease, grime, oil, waxes, gums, tars, etc.
- Non-flammable
- No 1,1,1 Trichloroethane or ozone depleting substances

SPECIFICATIONS

FORM: Solvent-Based Aerosol **ODOR: Chlorinated** COLOR: Clear, colorless **DETERGENCY: None** TOXICITY: 25 ppm OSHA TLV **WETTING ABILITY: Saturates** STORAGE STABILITY: 1 Year + COLD STABILITY: 0°F

PHOSPHATES: None

FLASH POINT: N/A FLAME EXTENSION: None **SOLUBILITY IN WATER: 0%** SPECIFIC GRAVITY: 1.6 % VOLATILE BY VOLUME: 100%

pH: N/A

PROPELLANT: Propane EVAPORATION RATE: Fast BIODEGRADABILITY: No

LABEL INFORMATION

PAD-KLEEN **BRAKE CLEANER**

PAD-KLEEN removes grease and tough grime from brake parts, linings and pads. Dries extremely fast and clean without residue. Nonflammable formula. Formulated to quickly and effectively remove grease, brake dust, brake fluids, oils and other contaminants. Cleans your brakes of build-up helping extend the life of your vehicle, while improving performance and keeping drivers safe.

DIRECTIONS: Do not use on plastics. Harmful to some paints. Pretest in a small area. Remove fluid and grease from linings and drums. Spray brake parts liberally and wipe clean with a cloth. Follow osha rules for brake parts with asbestos. DO NOT use forced air on asbestos brakes. Clean up spilled solvent immediately.

WARNING: Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of causing cancer. May cause an allergic skin reaction. May cause drowsiness or dizziness. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing dust/fume/gas/ mist/vapors/spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Dispose of contents and container in accordance with local, state, and national regulations.



WARNING: This product can expose you to chemicals including Tetrachloroethylene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Tetrachloroethyene (127-18-4) and Carbon Dioxide (124-38-9).

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	В



PACKAGING INFORMATION