



THE WORKS INTERIOR VINYL COATING









DESCRIPTION

THE WORKS is a clear interior coating which provides a fast drying glossy water barrier that brightens and beautifies vinyl and plastic. Just apply without wiping or buffing to achieve a long lasting shine without any runny residue. Contains a gloss boosting UV absorber. Leaves a pleasant watermelon scent.

APPLICATIONS

Perfect for use on Vehicle Interiors.

FEATURES & BENEFITS

- Water Resistant
- · Plastic Safe Solvent
- Clear With Watermelon Scent
- Instant Shine
- Will Not Streak

SPECIFICATIONS

FORM: Aerosol
ODOR: Watermelon
COLOR: Clear colorless
DETERGENCY: Excellent
TOXICITY: 500 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: Not Applicable, Aerosol

SOLUBILITY IN WATER: 100% SPECIFIC GRAVITY: 0.68-0.72 % VOLATILE BY VOLUME: 95%

pH: N/A

PROPELLANT: Hydrocarbon EVAPORATION RATE: Slow BIODEGRADABILITY: Yes

LABEL INFORMATION

THE WORKS INTERIOR VINYL COATING

THE WORKS is a clear coating which provides a fast drying glossy water barrier that brightens and beautifies vinyl and plastic surfaces.

- Product can also be sprayed into a clean, dry rag and applied if necessary.
- Coverage even into tight spaces.

DIRECTIONS FOR USE: Shake well before using. Prepare surface. Remove dirt, dust, oil and grease. Dry surface. Test spray on an inconspicuous area or scrap piece to check compatibility. Hold can 10" to 12" from surface. Use a stroking motion. Apply two or more coats rather than one heavy coat. For best results, spray at 70°F to 80°F. Polish surface, if desired, using a soft cloth after allowing spray to dry a few minutes.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause damage to the central and peripheral nervous systems, brain, lungs kidneys and reproductive system through prolonged or repeated exposure. Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Wash hands thoroughly after handling, take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs, get medical advice or attention. IF IN EYES: Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Avoid breathing mist, vapors or spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Use only outdoors or in a well-ventilated area. Call a poison center or doctor if you feel unwell. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Dispose of contents and container in accordance with local, state and federal regulations.



WARNING: Birth defects or other reproductive harm - www.P65Warnings.ca.gov.

CONTAINS (CAS#): Hexane (110-54-3), Butane (106-97-8), Propane (74-98-6), Dimethicone (63148-62-9), Benzyl Benzoate (120-51-4), Polymeric Benzotriazoles (104810-47-1 & 104810-48-2), Fragrance, Benzyl Salicylate. For more ingredient information please visit www.questspecialty.com.

MIR (0.99) meets 1.45 limit for vinyl/fabric/leather and plastic coating.

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	В



PACKAGING INFORMATION