

THUNDER

ORGANIC FOAMING ENGINE DEGREASER



DESCRIPTION

THUNDER works quickly to emulsify tar, asphalt, grease and oil. This product is safe and easy to use. Spray on and wash off with water. Dense foam allows product to cling to vertical surface allowing for longer contact time. Power spray cleans engines enabling them to run cooler, look better and last longer. Biodegradable and VOC compliant in all 50 states.

APPLICATIONS

Great for use on engines, appliances, road equipment, exhaust vents, motors, vehicles, rims, tools, refrigeration coils, machinery, industrial equipment, concrete, etc.

FEATURES & BENEFITS

- Dense clinging foam – will not run
- Spray on – wash off
- Dissolves oil, tar, grease, dirt, stains, road oil
- Cleans gasoline & diesel engines, metal, concrete, brick, stone

SPECIFICATIONS

FORM: Water-Based Aerosol	FLASH POINT: N/A
ODOR: Petroleum/Glycol	FLAME EXTENSION: None
COLOR: Milky White	SOLUBILITY IN WATER: 100%
DETERGENCY: Excellent	SPECIFIC GRAVITY: 0.994
TOXICITY: 25 ppm OSHA TLV	% VOLATILE BY VOLUME: 97%
WETTING ABILITY: Excellent	pH: 11
STORAGE STABILITY: 1 Year +	PROPELLANT: Hydrocarbon
COLD STABILITY: 32°F	EVAPORATION RATE: Slow
PHOSPHATES: None	BIODEGRADABILITY: Yes

LABEL INFORMATION

THUNDER ORGANIC FOAMING ENGINE DEGREASER

THUNDER works quickly to emulsify tar, asphalt, grease and oil. This product is safe and easy to use. Spray on and wash off with water. Dense foam allows product to cling to vertical surface allowing for longer contact time. Power spray cleans engines enabling them to run cooler, look better and last longer. Biodegradable and VOC compliant in all 50 states.

GREAT FOR THESE APPLICATIONS: Engines • Appliances • Road Equipment • Exhaust Vents • Motors • Vehicles • Rims • Tools Refrigeration Coils • Machinery • Industrial Equipment • Concrete • Etc.

DIRECTIONS FOR USE: When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar.

FOR ENGINES: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminum foil and run engine for fifteen minutes to insure complete drying.

OTHER SURFACES: To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

CONTAINS (CAS#): Water (7732-18-5), Propane/n-Butane (68476-86-8), Diethylene glycol n-butyl ether (112-34-5), Distillates (petroleum), hydrotreated light (64742-47-8), Nonionic Surfactant (127087-87-0).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 20 oz. cans per case, 17 oz. net weight