

# BIG RED

## SUPER IMPACT NON-MELT E.P. GREASE

### DESCRIPTION

**BIG RED** is a multi-use grease for hundreds of automotive, marine and agricultural applications. Extreme pressure additives give resistance to shock impact. Bentone based formula does not liquify at high temperatures like soap based greases, yet remains pumpable at low temperatures. Forms a protective film, resists rust and corrosion. Resists chemical break down and oxidation. This waterproof lubricant will not wash out even by boiling water and steam.

### APPLICATIONS

Excellent for use on high and low speed ball and roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, and fifth wheels. For use in all areas of industrial maintenance.

### FEATURES & BENEFITS

- High shock & impact resistance
- Extreme pressure additives for high loads
- Unique rust & corrosion inhibitors
- Wide temperature range
- All weather performance
- Resists: acids, water, salt spray, dust & dirt

### SPECIFICATIONS

**COLOR:** Red  
**THICKENER:** Bentone  
**NLGI GRADE:** 3  
**PENETRATION:** 220–250  
**DROPPING POINT:** Non-Melt  
**TEMPERATURE RANGE:** 0°F – 300°F

**TIMKEN OK LOAD:** 60–70 lbs.  
**BASE OIL:** Petroleum Oil  
**VISCOSITY @ 40°C:** 220 CST  
**FOUR BALL WELD LOAD:** 315–400 kg

### LABEL INFORMATION

#### BIG RED SUPER IMPACT NON-MELT E.P. GREASE


A multi-use grease for hundreds of automotive, marine and agricultural applications. Extreme pressure additives give resistance to shock impact. Bentone based formula does not liquify at high temperatures like soap based greases, yet remains pumpable at low temperatures. Forms a protective film, resists rust and corrosion. Resists chemical break down and oxidation. This waterproof lubricant will not wash out even by boiling water and steam.

**DIRECTIONS FOR USE:** Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

**CAUTION:** Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with soap and water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

**CONTAINS (CAS#):** Naphthenic Oil (64742-52-5), Nykon 77 (68953-58-2), Baragel 3000 (N/A), Paratac (0090003-27-4), Heavetex (9003-31-0).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



### PACKAGING INFORMATION

Available in 14 oz. cartridges (10/case), 35 lb. pails and 120 and 400 lb. drums.