

MR. GREEN

HIGH PERFORMANCE EXTREME CONDITION GREASE

DESCRIPTION

MR. GREEN is recommended for severe applications in many industries. It is particularly suitable for high speed bearings and centralized lubrication systems. **MR. GREEN** is recommended for use in automotive as well as extreme pressure applications. **MR. GREEN** is suitable anywhere where shear stable, high load carrying, corrosion resistant grease is required. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out. Resistant to corrosive salt water environments.

APPLICATIONS

For use on high and low speed ball and roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, and other severe service requirements. Areas of use include aircraft manufacturers, construction equipment manufacturers, new and used car dealers, automotive parts stores, farm machinery and equipment, highway paving contractors.

FEATURES & BENEFITS

- Calcium sulfonate grease with oxidation inhibitors & extreme pressure additives for severe applications
- Protects surfaces against corrosion and resulting seizing from fresh or salt water
- Suitable for high speed bearings & centralized lubrication systems
- Outstanding film strength

SPECIFICATIONS

COLOR: Green
THICKENER: Calcium Sulfonate
NLGI GRADE: 2
PENETRATION: 265–295
DROPPING POINT: +550°F
TEMPERATURE RANGE: -20°F – 500°F

TIMKEN OK LOAD: 65 lbs.
BASE OIL: Petroleum Oil
VISCOSITY: N/A
WHEEL BEARING LEAKAGE: 5.0 g Max
FOUR BALL WELD LOAD: 620 kg

LABEL INFORMATION

MR. GREEN HIGH PERFORMANCE EXTREME CONDITION GREASE

MR. GREEN is recommended for severe applications in many industries. It is particularly suitable for high speed bearings and centralized lubrication systems. **MR. GREEN** is recommended for use in automotive as well as extreme pressure applications. **MR. GREEN** is suitable anywhere where shear stable, high load carrying, corrosion resistant grease is required. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out. Resistant to corrosive salt water environments.


USES: Ball bearings, roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, construction, mining, agricultural, logging and hauling industries.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

CONTAINS (CAS#): Naphthenic Oil (64742-53-5), Calcium Sulfonate Complex (N/A).

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

Available in 14 oz. cartridges (10/case), 35 lb. pails, 120 and 400 lb. drums.