

# MR. JOE

## AMBER PREMIUM LITHIUM E.P. GREASE

### DESCRIPTION

**MR. JOE** is a multi-use lithium-complex grease for hundreds of automotive, marine, industrial and agricultural applications. Does not dry out after use as some clay based greases do. Remains pumpable at low temperatures. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out.

### APPLICATIONS

Excellent for use on high and low speed ball and roller bearings, couplings, mechanical linkages, pumps, universal joints, ball joints, fifth wheels, wheel bearings and chassis. For use in all areas of industrial maintenance.

### FEATURES & BENEFITS

- Resists thinning or hardening in medium sized high speed bearings
- Lithium grease with oxidation inhibitors & extreme pressure additives for a wide range of uses
- Protects surfaces against corrosion
- Operating range of 0°F to +350°F

### SPECIFICATIONS

**COLOR:** Amber  
**THICKENER:** Lithium Complex  
**NLGI GRADE:** 2  
**PENETRATION:** 265–295  
**DROPPING POINT:** 550°F – 600°F

**TIMKEN OK LOAD:** 60–70 lbs.  
**BASE OIL:** Petroleum Oil  
**VISCOSITY:** N/A  
**TEMPERATURE RANGE:** 0°F – 350°F  
**FOUR BALL WELD LOAD:** 315 kg

### LABEL INFORMATION

**MR. JOE**  
**AMBER PREMIUM LITHIUM E.P. GREASE**


**MR. JOE** is a multi-use lithium-complex grease for hundreds of automotive, marine, industrial and agricultural applications. Does not dry out after use as some clay based greases do. Remains pumpable at low temperatures. Forms protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This waterproof lubricant will not wash out.

**DIRECTIONS FOR USE:** Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

**CAUTION:** Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

**CONTAINS (CAS#):** Petroleum distillate, hydrotreated heavy naphthenic (64742-52-5), Lithium 12-hydroxystearate (7620-77-1), Lithium stearate (4485-12-5), Elco 102 (68649-42-3), Lubrizol7065 OPC (N/A).

HEALTH	0
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

Available in 14 oz. cartridges (10/case), 35 lb. pails and 120 and 400 lb. drums.