

QuestSpecialty

# NICKEL LUBE

## Anti-Seize / Antiagarre

Prevents Seizing & Galling • Protects at 2600 ° F  
Excellent Corrosion Prevention • Meets MIL-PRF-907E

**DANGER:** Causes damage to organs  
through prolonged or repeated exposure.

**PELIGRO:** PROVOCA DAÑOS EN  
LOS ÓRGANOS TRAS EXPOSICIONES  
PROLONGADAS O REPETIDAS.

**NET CONTENTS: 8 OZ.**

*NICKEL LUBE based anti-seize lubricant is non melt and will withstand extreme pressures and temperatures up to 2600°F. Seals out moisture, gases and corrosive fluids from threaded parts or any metal surface. Allows for the quick separation of mated parts after exposure to corrosive or hot environments.*

**Applications:** INDUSTRIAL: Nuts, valves, flanges, studs, threaded fittings, bushings, manifold surfaces, plugs, valve shafts, valve assemblies, gaskets, bolts, conveyors, gear reducers, transmission shafts, fans, blowers, compressor pumps, turbines, etc. STATIONARY AND MARINE ENGINES: Valve gauges and gaskets, fuel injectors, air starting valves, compressor gauges and piping, cylinder head gaskets and stud assemblies. TRUCK FLEETS: Cylinder head assemblies, exhaust manifold and turbo charger fittings, torque rod tubes and pins, brake anchor pins, air cylinder assemblies.

**Directions:** Clean surface to be treated. Apply with brush to insure contact over irregular areas.

**Instrucciones:** Limpiar la superficie a tratar. Aplicar con brocha para asegurar el contacto sobre áreas irregulares.

**DANGER:** Causes damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. Suspected of causing cancer. Obtain, read and follow all safety instructions before use. Do not breathe dust, fume, gas, mist, vapors. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective gloves, and protective clothing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical help. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. If exposed or concerned, get medical advice. Get medical help if you feel unwell. Store locked up. Dispose of contents and container in accordance with local, state and federal regulations.

**PELIGRO:** Provoca daños en los órganos tras exposiciones prolongadas o repetidas.

gadas o repetidas. Puede provocar una reacción alérgica en la piel. Se sospecha que causa cáncer. Obtenga, lea y siga todas las instrucciones de seguridad antes de su uso. No respirar el polvo, el humo, el gas, la niebla o los vapores. Lávese bien las manos después de manipular. No coma, beba ni fume mientras utiliza este producto. Utilice protección para los ojos, guantes protectores y ropa protectora. **EN CASO DE CONTACTO CON LA PIEL:** Lavar con abundante agua. Si se produce irritación o sarpullido en la piel: busque ayuda médica. Quítese la ropa contaminada y lávela antes de volver a usarla. No se debe permitir que la ropa de trabajo contaminada salga del lugar de trabajo. Si está expuesto o preocupado, busque atención médica. Busque ayuda médica si no se siente bien. Tienda cerrada. Deseche el contenido y el contenedor de acuerdo con las regulaciones locales, estatales y federales.



**WARNING:** Cancer and Reproductive Harm –  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**ADVERTENCIA:** Cáncer y daños reproductivos –  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**CONTAINS (CAS #):** Polybutene (9003-29-6), Nickel (7440-02-0), Aluminum (7429-90-5), Amorphous silica (112945-52-5), Distillates (petroleum), hydrotreated light (64742-47-8).

**HMS Ratings:** Health - \*2, Flammability - 1, Reactivity - 0, Personal - A.

**QuestSpecialty Corporation**  
P.O. Box 624, Brenham, TX 77834  
800.231.0454 • [www.questspecialty.com](http://www.questspecialty.com)

**ITEM L6760001-80Z** 600005676 Made in USA

