

PENETRANT GUIDE

5280 EASE

Food Grade Penetrating Oil

- Non-Flammable
- Penetrates • Lubricates
- Protects Against Rust
- Inhibits Corrosion
- Odorless, Colorless

5280-SDS AND PRODUCT INFO



5500/5090 PIERCE

Penetrating Lubricant

- Non-Flammable
- Non-Conducting
- Four Way Protection
- 30,000 Volt Dielectric

5500/5090-SDS & PRODUCT INFO



5690 CUT N' TAP

Cutting Oil

- Foaming Action to Cling to Tools
- For use on Ferris and Non Ferris Metals
- Extends Cutting Tool Life
- Cools and Lubricates

5690-SDS AND PRODUCT INFO



5330 GENESIS

Penetrant Lubricant

- Non-Flammable • Non-Chlorinated
- Non-Conducting
- Four Way Protection
- Prevents Rust & Displaces Moisture

5330-SDS AND PRODUCT INFO



5510 OUTBREAK

Cherry Penetrating Lubricant

- JQ Technology Quickly Breaks & Blasts Away Rust
- Rapid Penetrating Action Breaks Free Rusted Bolts
- Non-Flammable
- 50 State Compliant

5510-SDS & PRODUCT INFO



5740 SLICK

Lubricant

- Contains PTFE & Moly
- Loosens Nuts & Bolts • Lubricates
- Prevents Rust & Corrosion
- Displaces Moisture

5740-SDS AND PRODUCT INFO



5340/5350 MR. MECHANIC

Penetrating Lubricant

- Four Way Protection
- Cleans, Lubricates Prevents Rust

5340/5350-SDS & PRODUCT INFO



5530 SUPER PEN

Foaming Penetrant

- Non Chlorinated & No Silicone
- Breaks Through Tough Rust
- Creeps Between Parts For Safe Loosening
- Displaces Moisture & Prevents Rust

5530-SDS & PRODUCT INFO



5451 BREACH

Super Penetrant

- Breaks Up Rust
- Quickly Loosens Frozen Bolts
- Displaces Moisture
- Lubricating Action

5451-SDS AND PRODUCT INFO



5810 ULTRA TAC

High Pressure Penetrating Lubricant

- Contains PTFE • Non-Chlorinated
- Withstands Heat Up to 600°F
- Long Lasting Protection

5810-SDS AND PRODUCT INFO



5970 CHILL OUT

Freezing Penetrating Lubricant

- Freezing Action Unlocks Rusted Parts
- Non-conductive
- Non-chlorinated • Low VOC Content

5970-SDS AND PRODUCT INFO



5612 LIBERATE

Penetrant

- Contains PTFE & Moly for High Pressure Performance & Decreased Metal Wear
- Clinging Formula for Improved Lubricity & Coverage
- Does not Contain Silicone or Chlorinated Solvents

5612-SDS AND PRODUCT INFO



Features at a Glance

	5280 PEN EASE	5330 GENESIS	5340/5350 MR. MECHANIC	5451 BREACH	5500/5090 PIERCE	5510 OUTBREAK	5530 SUPER PEN	5612 LIBERATE	5690 CUT N' TAP	5740 SLICK	5810 ULTRA TAC	5970 CHILL OUT
Feature	Food Processing Friendly	4 Way Protection	4 Way Protection	Capillary Action	4 Way Protection	Premium Formula	Foaming	Clinging Formula	Cutting/Tapping Oil	Penetrating Lubricant	Sets up as Grease	Freezing Action
Performance	Light Duty	Light Duty	Light Duty	Heavy Duty	Light Duty	Medium Duty	Heavy Duty	Heavy Duty	Medium Duty	Medium Duty	Medium Duty	Medium Duty
Odor	Mild	Bland	Petroleum	Mild	Chlorinated	Cherry	Petroleum	Petroleum	Petroleum	Chlorinated	Chlorinated	Chlorinated
Evaporation	Slow	Slow	Slow	Slow	Medium	Slow	Fast	Slow	Slow	Slow	Slow	Medium
Silicone					No		No	No				
Color	Clear	Light Amber	Brown	Clear	Clear	Amber	Amber	Gray	Brown	Brown	Tan	Clear
50 State Compliant	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓
Dielectric		✓			✓							
Non-Flammable	✓	✓			✓	✓						
NSF	✓											
USDA			✓		✓							
PTFE											✓	
Moly							✓					
PTFE & Moly								✓		✓		
Non-Chlorinated		✓					✓	✓				✓



P.O. Box 624 • Brenham, TX 77834
 713.896.8188 • 800.231.0454
www.questspecialty.com