

Scan QR Code to
Check Out the Tech Sheet
from Our Website!



GRAPH-GUARD

QuestSpecialty
Corporation

GRAPH-GUARD

Dry Film Graphite Lubricant

GRAPH-GUARD dry film graphite lubricant offers superior, long-lasting performance where petroleum products must be avoided. Graphite anti-seize dry coating resists dust and abrasive particles. Withstands water, oil, alkalies and most acids. Forms a strong bond to metal—will not wipe off easily. May be used at higher temperatures than molybdenum disulfide based dry film lubricants. Formula is more readily accepted by safety directors. May be used as a release agent.



❖ **565000001-16AR Graph-Guard**
12–16 oz. cans/cs, 12 oz. net wt.

Areas Of Use:

*Foundries, Machine Shops, Industrial Plants, Automotive Manufacturers,
Steel Mills, Chemical Plants, Shipyards, Oil Fields,
Marine & Mining Operations And More.*

*Pipe Threads, Conveyors, Motors, Gaskets, Vending Machines,
Parking Meters, Chains And Sprockets, Pump Assemblies,
Road Equipment, Rollers, Wheels, Hoists and More.*

Features and Benefits:

*Temperature Range -100°F to +850°F
Dries to a Black, Tack-Free Film
Adheres to Metal, Glass, Rubber and Most Plastics
Resists Pressures Up To 18,000 psi
Resists Water Wash-out, Oils, Alkalies and Most Acids
Extends Metal Life*



P.O. Box 624 • Brenham, TX 77834
800.231.0454 • www.questspecialty.com

