Product # 5300

Technical Data Report

LOOSE SCREW

LUBRICANT & PENETRANT WITH PTFE



DESCRIPTION

LOOSE SCREW is a non-flammable, 4-in-1 formula that penetrates, lubricates, displaces moisture and resists corrosion. Displaces water and moisture from electrical equipment such as contact points and automotive distributors, machinery parts, guns and equipment. Fortified with PTFE. Contains no ozone depleters. Conforms to Military Specifications MIL-C-23411 for corrosion prevention. Due to VOC regulations, not available for sale in California and Utah.

APPLICATIONS

This lubricant is great for use on motors, wire cable, rusted parts, ignition systems, machine parts, door hinges, locks, nuts and bolts and refrigeration equipment. Used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, airlines, air maintenance shops, industrial plants, oil rigs, hotels/motels and general industries.

FEATURES & BENEFITS

- Non-Flammable
- 4-in-1 Lubricating & Penetrating Oil
- Displaces Moisture
- Contains PTFE to Inhibit Rust & Corrosion

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 100 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year
COLD STABILITY: 0°F
PHOSPHATES: N/A

FLASH POINT: N/D
FLAME EXTENSION: N/D
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.4-1.6
VOLATILE ORGANIC COMPOUNDS (VOC): 16.5%
pH: N/A
VISCOSITY: Thin
EVAPORATION RATE: N/D
BIODEGRADABILITY: No

LABEL INFORMATION

LOOSE SCREW
LUBRICANT & PENETRANT WITH PTFE

LOOSE SCREW is a non-flammable, 4-in-1 formula that penetrates, lubricates, displaces moisture and resists corrosion. Displaces water and moisture from electrical equipment such as contact points and automotive distributors, machinery parts, guns and equipment. This lubricant is used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, airlines, air maintenance shops and general industries. Fortified with PTFE. Contains no ozone depleters. Conforms to Military Specifications MIL-C-23411 for corrosion prevention.

RESTRICTIONS ON USE: Please see most recent SDS revised on 08/04/2025.

DIRECTIONS: Keep actuator pointed towards dot on valve cup. Remove cap. Direct spray toward area to be treated and spray generously until all moisture is rinsed away. Spraying action will also leave a protective coating to repel moisture. Repeat as needed. Can also be used to loosen rusty nuts and bolts.

DANGER: Pressurized container: may burst if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of causing cancer. May cause an allergic skin reaction. Harmful if inhaled. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing fumes, mist, vapors, and spray. Wear protective gloves, eye protection and protective clothing. Wash hands thoroughly after handling. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF SWALLOWED: Get emergency medical help immediately. Do NOT induce vomiting. IF EXPOSED OR CONCERNED: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state, and national regulations.

⚠ **WARNING:** This product can expose you to chemicals including Tetrachloroethylene (Perchloroethylene), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Petroleum Distillate (8052-41-3), Mineral Oil (8042-47-5), Carbon Dioxide (124-38-9), Barium sulfonate (Proprietary).

NOTE: This product, due to its chlorinated solvent content, is prohibited for sale and use in the State of California. Other areas may also prohibit its sale and use. Check local and state regulations.

HEALTH	3*
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

12 – 20 oz. cans per case, 19 oz. net weight