Product # 5370

Technical Data Report

SILI LUBE

HEAVY DUTY SILICONE SPRAY



DESCRIPTION

SILI LUBE is a multi-purpose silicone spray. Non-flammable formula is safe to use in plant areas. Formula uses a high viscosity silicone for long lasting lubrication and protection. Non-conductive to 28,000 volts. Stable temperatures up to 400°F. This formulation has been authorized for use in federally inspected meat and poultry plants by the USDA.

APPLICATIONS

Cleans, shines and leaves a protective film on rusted parts, wire cable, door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, block and tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Reduces metal-to-metal noises and rubber-to-metal squeaks
- Clean, non-staining formula
- Waterproof and rustproof
- Non-flammable

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear, Colorless to slight tint spray
DETERGENCY: None
TOXICITY: 100 ppm OSHA PEL
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: N/D

FLASH POINT: N/D
FLAME EXTENSION: N/D
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.5-1.6
VOLATILE ORGANIC COMPOUNDS (VOC): 0%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: N/D
BIODEGRADABILITY: No

LABEL INFORMATION

SILI LUBE
SILICONE SPRAY

Stops sticking of drawers, windows, doors, screens, zippers and locks. Eliminates annoying squeaks in hinges, latches and springs, etc. Stops car doors, locks and trunk moldings from sticking.

Retards corrosion – protects battery terminals, tools, guns, skates, aluminum windows and doors, etc. Waterproofs ignition systems and sparkplugs. Prevents jamming and production slow down. Contains no animal or vegetable fats. Absolutely neutral.

RESTRICTIONS ON USE: Please see most recent SDS revised on 07/22/2025.


DIRECTIONS: Thoroughly clean the surface to be sprayed. Spray a light film with a sweep motion. When used on sticking surfaces, work object back and forth. Spray again if necessary. **NOTE:** Product may harm some plastics TEST before using.

WARNING: Pressurized container: may burst if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause an allergic skin reaction. Harmful if inhaled. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. -No smoking. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing fumes, mist, vapors, and spray. Wear protective gloves, eye protection and protective clothing. Wash hands thoroughly after handling. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF EXPOSED OR CONCERNED: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get emergency medical help. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Tetrachloroethylene (Perchloroethylene), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Siloxanes and silicones, dimethyl (63148-62-9), Carbon Dioxide (124-38-9).

HEALTH	*2
FLAMMABILITY	0
REACTIVITY	1
PERSONAL	C



PACKAGING INFORMATION

12 – 16 oz. cans per case, 15 oz. net weight