



Technical Data Report

LEMONATOR CITRUS-BASED WATER SOLUBLE DEGREASER



DESCRIPTION

LEMONATOR is a high pressure, water soluble degreaser to flush away grease, tar and asphalt from hard surfaces. Contains no petroleum distillates.

APPLICATIONS

Degrease trucks, remove printer's ink, tire marks, soap scum, decals and adhesives, clean motors and equipment, de-tar vehicles, loosen chewing gum and candle wax from hard surfaces, clean fuel oil deposits from metal surfaces. Also use to clean and polish stainless steel and other metals. Areas of use include: Petroleum industry areas, sewage plants, service stations, garbage trucks, auto detailers, automotive plants, theaters, locker rooms, restrooms, schools, restaurants, office buildings, apartments, nursing homes, hospitals, commissaries.

FEATURES & BENEFITS

- Clean Lemon Odor
- Removes Grease, Tar and Asphalt
- No Petroleum Distillates

SPECIFICATIONS

FORM: Solvent-Based Aerosol
 ODOR: Citrus
 COLOR: Clear to Pale Yellow
 DETERGENCY: Excellent
 TOXICITY: OSHA OEL CO₂ propellant 5000 ppm
 WETTING ABILITY: N/A
 COLD STABILITY: 0°F
 PHOSPHATES: None
 FLASH POINT: N/D

FLAME EXTENSION: >18"
 SOLUBILITY IN WATER: Miscible
 SPECIFIC GRAVITY: 0.87-0.88
 % VOC: 95.1%
 pH: N/A
 PROPELLANT: Carbon Dioxide
 EVAPORATION RATE: N/D
 BIODEGRADABILITY: No

LABEL INFORMATION

LEMONATOR CITRUS-BASED WATER SOLUBLE DEGREASER

Lemonator is a high pressure water soluble degreaser to flush away grease, tar and asphalt from hard surfaces.

APPLICATIONS: Degrease trucks, remove printer's ink, tire marks, soap scum, decals and adhesives, clean motors and equipment, de-tar vehicles, loosen chewing gum and candle wax from hard surfaces, clean fuel oil deposits from metal surfaces. Also use to clean and polish stainless steel and other metals.

AREAS OF USE INCLUDE: Petroleum industry areas, sewage plants, service stations, garbage trucks, auto detailers, automotive plants, theaters, locker rooms, restrooms, schools, restaurants, office buildings, apartments, nursing homes, hospitals, commissaries.


DIRECTIONS: Spray directly onto surface to be treated. Let set for several seconds. Wipe off or flush clean with water.

NOTE: LEMONATOR may be harmful to plastics or painted surfaces. Always test surface in an inconspicuous area before using. Because LEMONATOR is a powerful grease solvent, it will defat skin. When using LEMONATOR, rubber gloves are recommended to avoid chapped skin. Do not spray into or on electrical equipment.

DANGER: Extremely flammable aerosol. Pressurized container: may burst if heated. Causes serious eye damage. Causes skin irritation. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Avoid breathing mist, vapors, spray. Wear protective gloves, eye protection, face protection, and protective clothing. Wash hands thoroughly after handling. Do not touch eyes. **IF IN EYES:** Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get emergency medical help. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of water. If skin irritation or rash occurs: Get medical help. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Dispose of contents and container in accordance with local, state and national regulations.

CONTAINS (CAS#): Hydrocarbons, Terpene processing, by-product (68956-56-9), d-Limonene (5989-27-5), Alcohols, C6-12, ethoxylated propoxylated (68937-66-6), Alcohols, C10-16, ethoxylated propoxylated (69227-22-1), Carbon Dioxide (124-38-9).

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	D



PACKAGING INFORMATION

12 – 20 oz. cans per case, 16 oz. net weight