

Technical Data Report

MOLI DRI

Dry Moly Lubricant



DESCRIPTION

MOLI DRI is a dry film lubricant without harmful chlorinated solvents providing excellent pressure and temperature resistance. Molybdenum and graphite anti-seize dry coating resists dust and abrasive particles. Withstands water, oil, alkalis and most acids. Quick drying to prevent run off and allows for use immediately.

APPLICATIONS

Oil drilling equipment, pipe threads, lathe bed and rails, chains and sprockets, road equipment, door locks and hinges, etc. Also may be used as a release agent.

FEATURES & BENEFITS

- Non-Conductive Dry Film
- Quick Drying with No Grease or Oil
- Temperatures Range - 100°F to 850°F
- No Chlorinated Solvents

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Solvent
COLOR: Black Soft Misting Cone
DETERGENCY: N/A
TOXICITY: 200 PPM OSHA PEL
WETTING ABILITY: None
STORAGE STABILITY: 1 Year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: > 18"
SOLUBILITY IN WATER: Negligible
SPECIFIC GRAVITY: 0.90g/ml
% VOC: 60%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Component(s) may degrade over time

LABEL INFORMATION

MOLI DRI DRY MOLY LUBRICANT

Dry film lubricant without harmful chlorinated solvents providing excellent pressure and temperature resistance. Molybdenum and graphite anti-seize dry coating resists dust and abrasive particles. Withstands water, oil, alkalis and most acids. Quick drying to prevent run off and allows for use immediately.

RECOMMENDED FOR: Foundries; machine shops; automotive plants; vehicle maintenance; sewing trades; paper and corrugated converting; chemical plants; marine, oil field, and mining operations; etc.

APPLICATIONS: Oil drilling equipment, pipe threads, lathe bed and rails, chains and sprockets, road equipment, door locks and hinges, etc. Also may be used as a release agent.


DIRECTIONS FOR USE: Shake container well before using. Clean surface thoroughly. Hold 8 to 12" from surface and apply a thin, even film. Thick coats decrease efficiency. Dries in 1 to 3 minutes. Allow to cure 30 minutes before exposing to water.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to central nervous system (CNS), liver, kidneys and respiratory system through prolonged or repeated exposure. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Obtain, read and follow all safety instructions before use. Wash hands thoroughly after handling. Wear protective gloves and eye protection. Do not eat, drink or smoke when using this product. **IF ON SKIN:** Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If exposed or concerned: Get medical advice or attention immediately. Do not breathe the mist, vapor and spray. Use only outdoors or in a well-ventilated area. Dispose of contents and container in accordance with local, state and federal regulations.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

INGREDIENTS (CAS#): Acetone (67-64-1), Toluene (108-88-3), Propane (74-98-6), Butane (106-97-8), Isopropyl Alcohol (67-63-0).

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

12 – 16 oz. cans per case, 11 oz. net weight