

ARC

Water-Based Anti-Spatter



DESCRIPTION

ARC is a water-based formula that is economical and safe. This silicone free formula provides an efficient and effective coating that stops the formation of spatter build up on nozzles, tips, and metal surfaces. Residual spatter is easily wiped away instead of using a chisel, grinder, or wire brush saving you time. Once welding is complete the coating can be quickly removed by wiping with a cloth or rinsing with water or a solvent to allow for paint.

APPLICATIONS

For use on bench top splash guards, contact tips, electrode holders, metal molds, Mig and Tig tips, resistance welding tips, tools, and weldments.

FEATURES & BENEFITS

- Non-Flammable and Non-Toxic
- Prevents Flash Rusting and Spatter Build Up
- Silicone Free
- No Chlorinated Solvents

SPECIFICATIONS

<p>FORM: Water-Based Aerosol ODOR: Mild Odor COLOR: White Aerosol spray DETERGENCY: N/A TOXICITY: 5mg/m3 OSHA PEL WETTING ABILITY: N/D STORAGE STABILITY: 1 Year + COLD STABILITY: 32°F PHOSPHATES: None</p>	<p>FLASH POINT: N/A FLAME EXTENSION: > 18" SOLUBILITY IN WATER: Miscible SPECIFIC GRAVITY: 0.97g/ml % VOC: 25% pH: 7 PROPELLANT: Hydrocarbon EVAPORATION RATE: Slow BIODEGRADABILITY: No</p>
---	--

LABEL INFORMATION

ARC WATER-BASED ANTI-SPATTER

Water-based formula is economical and safe. This silicone free formula provides an efficient and effective coating that stops the formation of spatter build up on nozzles, tips, and metal surfaces. Residual spatter is easily wiped away instead of using a chisel, grinder, or wire brush saving you time. Once welding is complete the coating can be quickly removed by wiping with a cloth or rinsing with water or a solvent to allow for paint.

APPLICATIONS:


For use on bench top splash guards, contact tips, electrode holders, metal molds, Mig and Tig tips, resistance welding tips, tools, and weldments.

DIRECTIONS FOR USE: Shake container well before using. Clean surface before application. Holding can 8-12" from the surface, spray a light film evenly over the area to be welded as well as the tips and nozzles. After welding job is complete wipe or rinse treated areas before painting or reapplying if necessary.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Water (7732-18-5), Butane (106-97-8), Mineral Oil (8042-47-5), Propane (74-98-6), Sorbitan Oleate (1332-43-8).

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 16 oz. cans per case, 14 oz. net weight