

MC FREE SURROUND

COLD PIPE INSULATION SPRAY



DESCRIPTION

MC FREE SURROUND is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard to reach areas. Expanding spray conforms to irregularly shaped surfaces.

APPLICATIONS

For use on cold water pipes, valves and fittings, metal gutters, refrigeration lines, condenser lines and water tanks. Areas of use include air conditioning maintenance, aircraft maintenance, industrial operations, food plants, refrigeration trucks, cold storage lockers, shipping operations, kitchens and indoor ice rinks.

FEATURES & BENEFITS

- Durable finish may be painted or primed
- Repairs wrap around pipe insulation, prolonging life
- Water resistant coating prevents condensation and dripping

SPECIFICATIONS

FORM: Solvent Based Aerosol	VOC CONTENT: 33.4%
ODOR: Alcohol	FLASH POINT: N/A
COLOR: White	FLAME EXTENSION: >18"
DETERGENCY: N/D	SOLUBILITY IN WATER: Miscible
TOXICITY: 1000 ppm OSHA PEL	SPECIFIC GRAVITY: 0.81
WETTING ABILITY: N/D	pH: N/A
STORAGE STABILITY: 1 Year +	PROPELLANT: Hydrocarbon
COLD STABILITY: 32°F	EVAPORATION RATE: N/D
PHOSPHATES: None	BIODEGRADABILITY: Partially

LABEL INFORMATION

MC FREE SURROUND COLD PIPE INSULATION SPRAY

MC FREE SURROUND is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard to reach areas. Expanding spray conforms to irregularly shaped surfaces.

DIRECTIONS: Remove dust and loose dirt from surface to be sprayed by wiping with clean, dry cloth. Cover surfaces under area to be treated to avoid overspray. Shake can vigorously. Continue shaking for one minute and occasionally during use. For proper adhesion apply only to dry surfaces. Hold can 8-10" from surface. Apply with a sweeping motion using several thin coats. Allow each coat to dry thoroughly for several minutes before applying a new coat. If product runs, can is too close to surface.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. Keep away from heat, sparks, open flames or hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.

CONTAINS (CAS#): Acetone (67-64-1), Propane (74-98-6), Butane (106-97-8), Ethyl Acetate (141-78-6), Stearic Acid (57-11-4).

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 - 20 oz. cans per case, 14 oz. net weight