



Product # 5930

Technical Data Report

PIERCE II

PENETRATING LUBRICANT



DESCRIPTION

PIERCE II is a high-performance, four-way penetrating lubricant engineered to penetrate, clean, lubricate and protect. Its aggressive formula quickly works into rusted and corroded components, displaces moisture and helps free stuck or difficult-to-move parts.

The versatile formulation delivers reliable lubrication while leaving behind a protective rust-preventative film to help guard against future corrosion. Its powerful penetrating action makes PIERCE II an ideal choice for maintenance, repair and industrial applications where performance matters.

PIERCE II is flammable and non-conductive to 6,000 volts, making it a versatile solution for a wide range of maintenance and service applications.

APPLICATIONS

For use on Start Wet Engines, Freeing Nuts & Bolts, Electrical Panel Board, Parking Meters, Remove Moisture from Ignition Wires, Stops Corrosion on Battery Terminals, Airplanes, Vending Machines, Laundromats, Refrigeration Equipment

FOUR-WAY PERFORMANCE

- **Penetrates** — Quickly works into rust, corrosion and seized components.
- **Cleans** — Breaks down dirt, grime and contaminants.
- **Lubricates** — Reduces friction and helps restore smooth operation.
- **Protects** — Leaves a rust-preventative film to help protect against corrosion.

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear, colorless spray
DETERGENCY: None
TOXICITY: 200 ppm OSHA PEL TWA
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/D
FLAME EXTENSION: >15 cm
SOLUBILITY IN WATER: Negligible
SPECIFIC GRAVITY: 1.05 - 1.15
% VOC: 25%
pH: N/A
PROPELLANT: Carbon Dioxide
EVAPORATION RATE: Medium
BIODEGRADABILITY: No

LABEL INFORMATION

PIERCE II PENETRATING LUBRICANT

Pierce II penetrating lubricant is a powerful, multiple-action penetrant and protective shield. Can be used on either dry or wet surfaces. To ensure adequate protection, periodic checks should be made to determine the need for reapplication.

SUGGESTED USES


- Start Wet Engines
- Freeing Nuts & Bolts
- Laundromats
- Airplanes
- Electrical Panel Board
- Parking Meters
- Refrigeration Equipment
- Vending Machines
- Remove Moisture from Ignition Wires
- Stops Corrosion on Battery Terminals

DIRECTIONS: Spray liberally directly on area to be treated. Reapply periodically as required.

DANGER: Flammable aerosol. Pressurized container: may burst if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. IF ON SKIN: Wash with plenty of water. IF SKIN irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice or attention. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Store in a well-ventilated place. Keep container tightly closed. IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state and federal regulations.

CONTAINS (CAS#): Propylene Carbonate (108-32-7), Methyl Acetate (70-20-9), Trans-1,2-Dichloroethylene (CAS 156-60-5), Carbon dioxide (124-38-9), Distillates (Petroleum), hydrotreated light (64742-47-8).

HEALTH	3
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 – 16 oz. cans per case, 16 oz. net weight.