



## Technical Data Report

# SMOOTH RIDE

## RUBBERIZED UNDERCOATING



### DESCRIPTION

Heavy duty black rubberized undercoating offers durable surface protection without the mess or odor of asphalt-based products. The fast drying formula leaves a flexible, smooth, uniform layer that won't crack, chip, flake, or peel off. Formula seals out moisture and salt to prevent rust and corrosion and is paintable in 1 hour. The built-in sound-deadening properties make it ideal for reducing road noise and vibrations in wheel wells, underbodies, rocker panels, and more.

### APPLICATIONS

Vehicle undercarriages, Hoods, Wheel wells, Rocker panels, Trunk interiors, Truck beds (beneath bedliners), Fender liners, Door skins and inner panels, weld joints, RV and trailer undersides, Agricultural and industrial equipment, and Marine trailers. Can also seal flashing, gutters, and cracks in concrete or asphalt. Patch roofs, planters, and tree wounds.

### FEATURES & BENEFITS

- Flexible Rubberized Coating
- Prevents Rust and Corrosion
- True Black Color
- Paintable
- Deadens Sound

### SPECIFICATIONS

**FORM:** Aerosol**ODOR:** Solvent**COLOR:** Black**DETERGENCY:** N/A**TOXICITY:** 100 ppm OSHA PEL**WETTING ABILITY:** N/A**COLD STABILITY:** 32°F**PHOSPHATES:** None**FLASH POINT:** N/A Aerosol**SOLUBILITY IN WATER:** 0%**SPECIFIC GRAVITY:** 1.26**% VOLATILE BY VOLUME:** 52.6%**pH:** N/A**PROPELLANT:** Hydrocarbon**EVAPORATION RATE:** Fast**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### SMOOTH RIDE RUBBERIZED UNDERCOATING

Heavy duty black rubberized undercoating offers durable surface protection without the mess or odor of asphalt-based products. The fast drying formula leaves a flexible, smooth, uniform layer that won't crack, chip, flake, or peel off. Formula seals out moisture and salt to prevent rust and corrosion and is paintable in 1 hour. The built-in sound-deadening properties make it ideal for reducing road noise and vibrations in wheel wells, underbodies, rocker panels, and more.

**RECOMMENDED FOR:** Vehicle undercarriages, Hoods, Wheel wells, Rocker panels, Trunk interiors, Truck beds (beneath bedliners), Fender liners, Door skins and inner panels, weld joints, RV and trailer undersides, Agricultural and industrial equipment, and Marine trailers. Can also seal flashing, gutters, and cracks in concrete or asphalt. Patch roofs, planters, and tree wounds.

**DIRECTIONS FOR USE:** Shake container for 30 seconds before using. Clean surface thoroughly. Hold 8 to 12" from surface and apply an even film. Allow 5-10 minutes to dry before adding further coats. Wait 30 minutes before adding final topcoat. For best results use when can is 74°F. Dry times can be affected by temperature and humidity. After use, invert can and spray until only gas is dispensed to prevent clogging.


**DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. Suspected of causing cancer, damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection. Wash hands and face thoroughly after handling. Do not breathe dust, fume, gas, mist, vapors, spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container to an approved waste disposal plant. **FIRST AID:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice, attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice, attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor, physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor, physician. Do NOT induce vomiting.

**Warning:** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Contains (CAS#):** Calcium Carbonate (1317-65-3), Toluene (108-88-3), Methyl Acetate (79-20-9), Hydrocarbon Resin (Mixture), Propane/Isobutane/N-Butane (68476-86-8), Acetone (67-64-1), Styrene-Butadiene Copolymer (9003-55-8), Organoclay (68911-87-5), bis(2-ethylhexyl)terephthalate(6422-86-2), Methanol (67-56-1), Carbon Black (1333-86-4).

**V.O.C. CONTENT:** 37.61% by Weight, 3.95 lbs/gal, 473.33 g/l, 0.458 lbs/can

HEALTH	*3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	C



### PACKAGING INFORMATION

12 - 20 oz. cans per case, 16 oz. net weight.