

NICKEL LUBE

ANTI-SEIZE



DESCRIPTION

NICKEL LUBE based anti-seize lubricant is non melt and will withstand extreme pressures and temperatures up to 2600°F. Seals out moisture, gases and corrosive fluids from threaded parts or any metal surface. Allows for the quick separation of mated parts after exposure to corrosive or hot environments.

APPLICATIONS

INDUSTRIAL: Nuts, valves, flanges, studs, threaded fittings, bushings, manifold surfaces, plugs, valve shafts, valve assemblies, gaskets, bolts, conveyors, gear reducers, transmission shafts, fans, blowers, compressor pumps, turbines, etc. **STATIONARY AND MARINE ENGINES:** Valve gauges and gaskets, fuel injectors, air starting valves, compressor gauges and piping, cylinder head gaskets and stud assemblies. **TRUCK FLEETS:** Cylinder head assemblies, exhaust manifold and turbo charger fittings, torque rod tubes and pins, brake anchor pins, air cylinder assemblies.

FEATURES & BENEFITS

- Prevents Seizing & Galling
- Excellent Corrosion Prevention
- Protects at 2600°F
- Meets MIL-PRF-907E

SPECIFICATIONS

<p>FORM: Thick Silver grease ODOR: Bland COLOR: Silver gray DETERGENCY: N/A TOXICITY: 1mg/m³ OSHA PEL WETTING ABILITY: N/A STORAGE STABILITY: 1 Year + COLD STABILITY: N/D PHOSPHATES: None</p>	<p>FLASH POINT: N/D BOILING POINT: N/D SOLUBILITY IN WATER: 0% SPECIFIC GRAVITY: 1.06-1.10 % VOC: 0% pH: N/A VISCOSITY: N/D EVAPORATION RATE: N/D BIODEGRADABILITY: No</p>
---	---

LABEL INFORMATION

NICKEL LUBE ANTI-SEIZE

NICKEL LUBE based anti-seize lubricant is non melt and will withstand extreme pressures and temperatures up to 2600°F. Seals out moisture, gases and corrosive fluids from threaded parts or any metal surface. Allows for the quick separation of mated parts after exposure to corrosive or hot environments.

Applications: **INDUSTRIAL:** Nuts, valves, flanges, studs, threaded fittings, bushings, manifold surfaces, plugs, valve shafts, valve assemblies, gaskets, bolts, conveyors, gear reducers, transmission shafts, fans, blowers, compressor pumps, turbines, etc. **STATIONARY AND MARINE ENGINES:** Valve gauges and gaskets, fuel injectors, air starting valves, compressor gauges and piping, cylinder head gaskets and stud assemblies. **TRUCK FLEETS:** Cylinder head assemblies, exhaust manifold and turbo charger fittings, torque rod tubes and pins, brake anchor pins, air cylinder assemblies.

Directions: Clean surface to be treated. Apply with brush to insure contact over irregular areas.

DANGER: Causes damage to organs through prolonged or repeated exposure. May cause an allergic skin reaction. Suspected of causing cancer. Obtain, read and follow all safety instructions before use. Do not breathe dust, fume, gas, mist, vapors. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective gloves, and protective clothing. **IF ON SKIN:** Wash with plenty of water. If skin irritation or rash occurs: Get medical help. Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. If exposed or concerned, get medical advice. Get medical help if you feel unwell. Store locked up. Dispose of contents and container in accordance with local, state and federal regulations.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

CONTAINS (CAS #): Polybutene (9003-29-6), Nickel (7440-02-0), Aluminum (7429-90-5), Amorphous silica (112945-52-5), Distillates (petroleum), hydrotreated light (64742-47-8).

HEALTH	*2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

Available in 8 oz. brush top cans (12/case).